

**FAG****7007-B-XL-2RS-TVP-P5-UO**

Angular contact ball bearing

Angular contact ball bearing 70..-B-XL-2RS-TVP, single row, X-life, seals, plastic cage

**X-life**

Technical information



Your current product variant

Design variant	B	B
Sealing	2RS	Contact seal on both sides
Cage	TVP	Solid cage made of glass-fiber reinforced polyamid PA66
Tolerance class	P5	Class 5 (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Bearing with matched conditions for fitting in pairs	UO	Bearing set clearance-free in O or X arrangement
Lubricant	GA14	Ball bearing grease, low noise

Main Dimensions & Performance Data

d	35 mm	Bore diameter
D	62 mm	Outside diameter
B	14 mm	Width
C_r	24.300 N	Basic dynamic load rating, radial
C_{0r}	17.200 N	Basic static load rating, radial
C_{ur}	1.200 N	Fatigue load limit, radial
n_G	6.000 1/min	Limiting speed
m	0,14 kg	Weight



Mounting dimensions

$d_{a \min}$	39,6 mm	Minimum diameter of shaft shoulder
$D_{a \max}$	57,4 mm	Maximum diameter of housing shoulder
$D_{b \max}$	58,8 mm	Maximum diameter of housing shoulder
$r_{a \max}$	1 mm	Maximum fillet radius of shaft
$r_{a1 \max}$	0,6 mm	Maximum fillet radius of housing

Dimensions

r_{\min}	1 mm	Minimum chamfer dimension
$r_{1 \min}$	0,6 mm	Minimum chamfer dimension
D_1	53,36 mm	Shoulder diameter on outer ring wide side face
D_2	54 mm	Caliber diameter on outer ring wide side face
D_3	58,94 mm	Caliber diameter on outer ring small side face
d_1	47,02 mm	Shoulder diameter on inner ring wide side face
d_2	43,64 mm	Caliber diameter on inner ring wide side face
a	27,9 mm	Distance between the apexes of the pressure cones
α	40 °	Contact angle

Temperature range

T_{\min}	-20 °C	Operating temperature min.
T_{\max}	100 °C	Operating temperature max.

Additional information

A_{\min}	0 μm	Axial clearance per set min.
Tol (+)	6 μm	Tolerance for axial clearance or preload per set



Characteristics



Radial load



Axial load in one direction



Lifetime lubrication, freedom from maintenance



Grease Lubrication



Sealed on both sides