

FAG

7008-B-XL-TVP [↗](#)

Angular contact ball bearing

Angular contact ball bearing 70..-B-XL-TVP,
single row, X-life, plastic cage

X-life

Technical information




Your current product variant

Design variant	B	B
Sealing	Without	Not sealed
Cage	TVP	Solid cage made of glass-fiber reinforced polyamid PA66
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Lubricant	Without	Bearing not greased

Main Dimensions & Performance Data

d	40 mm	Bore diameter
D	68 mm	Outside diameter
B	15 mm	Width
C_r	28.000 N	Basic dynamic load rating, radial
C_{0r}	20.300 N	Basic static load rating, radial
C_{ur}	1.410 N	Fatigue load limit, radial
n_G	13.300 1/min	Limiting speed
n_{gr}	8.400 1/min	Reference speed
$\approx m$	0,17 kg	Weight





Mounting dimensions

$d_{a \min}$	44,6 mm	Minimum diameter of shaft shoulder
$D_{a \max}$	63,4 mm	Maximum diameter of housing shoulder
$D_{b \max}$	64,8 mm	Maximum diameter of housing shoulder
$r_{a \max}$	1 mm	Maximum fillet radius of shaft
$r_{a1 \max}$	0,6 mm	Maximum fillet radius of housing






Dimensions

r_{\min}	1 mm	Minimum chamfer dimension
$r_{1 \min}$	0,6 mm	Minimum chamfer dimension
D_1	58,76 mm	Shoulder diameter on outer ring wide side face
D_2	59,39 mm	Caliber diameter on outer ring wide side face
D_3	64,95 mm	Caliber diameter on outer ring small side face
d_1	51,87 mm	Shoulder diameter on inner ring wide side face
d_2	48,33 mm	Caliber diameter on inner ring wide side face
a	30,5 mm	Distance between the apexes of the pressure cones
α	40 °	Contact angle

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	120 °C	Operating temperature max.

Characteristics

	Radial load
	Axial load in one direction
	Grease Lubrication
	Oil Lubrication
	Not sealed