

**FAG****7032-MP-UO**

Angular contact ball bearing

Angular contact ball bearing 70..-MP, single row, solid brass cage



Technical information

**Your current product variant**

Sealing	Without	Not sealed
Cage	MP	Solid brass cage, ball guided
Tolerance class	PN	Normal (PN)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Bearing with matched conditions for fitting in pairs	UO	Bearing set clearance-free in O or X arrangement
Lubricant	Without	Bearing not greased

Main Dimensions & Performance Data

d	160 mm	Bore diameter
D	240 mm	Outside diameter
B	38 mm	Width
C_r	160.000 N	Basic dynamic load rating, radial
C_{0r}	200.000 N	Basic static load rating, radial
C_{ur}	7.400 N	Fatigue load limit, radial
n_G	4.100 1/min	Limiting speed
n_{gr}	2.950 1/min	Reference speed
$\approx m$	5,76 kg	Weight



Mounting dimensions

$d_{a \min}$	170,2 mm	Minimum diameter of shaft shoulder
$D_{a \max}$	229,8 mm	Maximum diameter of housing shoulder
$D_{b \max}$	234 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2,1 mm	Maximum fillet radius of shaft
$r_{a1 \max}$	1 mm	Maximum fillet radius of housing

Dimensions

r_{\min}	2,1 mm	Minimum chamfer dimension
$r_{1 \min}$	1,1 mm	Minimum chamfer dimension
D_1	208 mm	Shoulder diameter on outer ring wide side face
d_1	192,4 mm	Shoulder diameter on inner ring wide side face
a	76,7 mm	Distance between the apexes of the pressure cones
α	30 °	Contact angle

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	150 °C	Operating temperature max.

Additional information

A_{\min}	0 μm	Axial clearance per set min.
Tol (+)	12 μm	Tolerance for axial clearance or preload per set

Characteristics

	Radial load
	Axial load in one direction
	Grease Lubrication
	Oil Lubrication
	Not sealed