

**FAG****7072-MP-UA**

Angular contact ball bearing

Angular contact ball bearing 70..-MP, single row, solid brass cage



Technical information

**Your current product variant**

Sealing	Without	Not sealed
Cage	MP	Solid brass cage, ball guided
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°
Bearing with matched conditions for fitting in pairs	UA	Bearing set with small axial internal clearance
Lubricant	Without	Bearing not greased

Main Dimensions & Performance Data

d	360 mm	Bore diameter
D	540 mm	Outside diameter
B	82 mm	Width
C_r	540.000 N	Basic dynamic load rating, radial
C_{0r}	1.090.000 N	Basic static load rating, radial
C_{ur}	27.000 N	Fatigue load limit, radial
n_G	1.700 1/min	Limiting speed
n_{gr}	1.090 1/min	Reference speed
$\approx m$	62,7 kg	Weight



Mounting dimensions

$d_{a \min}$	378 mm	Minimum diameter of shaft shoulder
$D_{a \max}$	522 mm	Maximum diameter of housing shoulder
$D_{b \max}$	531,2 mm	Maximum diameter of housing shoulder
$r_{a \max}$	4 mm	Maximum fillet radius of shaft
$r_{a1 \max}$	2 mm	Maximum fillet radius of housing

Dimensions

r_{\min}	5 mm	Minimum chamfer dimension
$r_{1 \min}$	2 mm	Minimum chamfer dimension
D_1	474,75 mm	Shoulder diameter on outer ring wide side face
d_1	429,25 mm	Shoulder diameter on inner ring wide side face
a	170,9 mm	Distance between the apexes of the pressure cones
α	30 °	Contact angle

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	200 °C	Operating temperature max.

Additional information

A_{\min}	172 μm	Axial clearance per set min.
Tol (+)	20 μm	Tolerance for axial clearance or preload per set



Characteristics

-  Radial load
-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Large bearing