

**FAG****7036-XL-MP**

Angular contact ball bearing

Angular contact ball bearing 70.-XL-MP,
single row, X-life, solid brass cage**X-life**

Technical information



Your current product variant

Sealing	Without	Not sealed
Cage	MP	Solid brass cage, ball guided
Tolerance class	PN	Normal (PN)
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°
Lubricant	Without	Bearing not greased

Main Dimensions & Performance Data

d	180 mm	Bore diameter
D	280 mm	Outside diameter
B	46 mm	Width
C _r	240.000 N	Basic dynamic load rating, radial
C _{0r}	295.000 N	Basic static load rating, radial
C _{ur}	13.400 N	Fatigue load limit, radial
n _G	3.800 1/min	Limiting speed
n _{gr}	2.550 1/min	Reference speed
≈m	9,78 kg	Weight





Mounting dimensions

$d_{a \min}$	190,2 mm	Minimum diameter of shaft shoulder
$D_{a \max}$	269,8 mm	Maximum diameter of housing shoulder
$D_{b \max}$	274 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2,1 mm	Maximum fillet radius of shaft
$r_{a1 \max}$	1 mm	Maximum fillet radius of housing

Dimensions

r_{\min}	2,1 mm	Minimum chamfer dimension
$r_{1 \min}$	1,1 mm	Minimum chamfer dimension
D_1	244,15 mm	Shoulder diameter on outer ring wide side face
d_1	218 mm	Shoulder diameter on inner ring wide side face
a	89,4 mm	Distance between the apexes of the pressure cones
α	30 °	Contact angle

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	200 °C	Operating temperature max.

Characteristics

	Radial load
	Axial load in one direction
	Grease Lubrication
	Oil Lubrication
	Not sealed