

**FAG****71892-MP-P5**

Angular contact ball bearing

Angular contact ball bearing 718.-MP, single row, solid brass cage



Technical information

**Your current product variant**

Type of seal	Without	Not sealed
Cage	MP	Solid brass cage, ball guided
Tolerance class	P5	Class5 (P5), better than P6
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°
Lubricant	Without	Bearing not greased

Main Dimensions & Performance Data

d	460 mm	Bore diameter
D	580 mm	Outside diameter
B	56 mm	Width
C_r	380.000 N	Basic dynamic load rating, radial
C_{0r}	740.000 N	Basic static load rating, radial
C_{ur}	19.100 N	Fatigue load limit, radial
n_G	1.550 1/min	Limiting speed
n_{gr}	870 1/min	Reference speed
$\approx m$	32,2 kg	Weight



Mounting dimensions

$d_{a \min}$	472 mm	Minimum diameter of shaft shoulder
$D_{a \max}$	568 mm	Maximum diameter of housing shoulder
$D_{b \max}$	574 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2,5 mm	Maximum fillet radius of shaft
$r_{a1 \max}$	1 mm	Maximum fillet radius of housing

Dimensions

r_{\min}	3 mm	Minimum chamfer dimension
$r_{1 \min}$	1,1 mm	Minimum chamfer dimension
D_1	536,85 mm	Shoulder diameter on outer ring wide side face
d_1	505,95 mm	Shoulder diameter on inner ring wide side face
a	178,1 mm	Distance between the apexes of the pressure cones
α	30 °	Contact angle

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	200 °C	Operating temperature max.

Characteristics

	Radial load
	Axial load in one direction
	Grease Lubrication
	Oil Lubrication
	Not sealed
	Large bearing