

**FAG****71968-MP-P6**

Angular contact ball bearing

Angular contact ball bearing 719..-MP, single row, solid brass cage



Technical information



Your current product variant

Type of Seal	Without	Not sealed
Cage	MP	Solid brass cage, ball guided
Tolerance class	P6	Class 6 (ISO 492:2023)
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°
Lubricant	Without	Bearing not greased

Main Dimensions & Performance Data

d	340 mm	Bore diameter
D	460 mm	Outside diameter
B	56 mm	Width
C_r	340.000 N	Basic dynamic load rating, radial
C_{0r}	580.000 N	Basic static load rating, radial
C_{ur}	17.900 N	Fatigue load limit, radial
n_G	2.010 1/min	Limiting speed
n_{gr}	1.250 1/min	Reference speed
$\approx m$	25,6 kg	Weight





Mounting dimensions

$d_{a \min}$	352,4 mm	Minimum diameter of shaft shoulder
$D_{a \max}$	447,6 mm	Maximum diameter of housing shoulder
$D_{b \max}$	454 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2,5 mm	Maximum fillet radius of shaft
$r_{a1 \max}$	1 mm	Maximum fillet radius of housing

Dimensions

r_{\min}	3 mm	Minimum chamfer dimension
$r_{1 \min}$	1,1 mm	Minimum chamfer dimension
D_1	412,6 mm	Shoulder diameter on outer ring wide side face
d_1	385,3 mm	Shoulder diameter on inner ring wide side face
a	143,5 mm	Distance between the apexes of the pressure cones
α	30 °	Contact angle

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	200 °C	Operating temperature max.

Characteristics

	Radial load
	Axial load in one direction
	Grease Lubrication
	Oil Lubrication
	Not sealed
	Large bearing