

**FAG****71976-MP-P5-UL**

Angular contact ball bearing

Angular contact ball bearing 719...-MP, single row, solid brass cage



## Technical information



## Your current product variant

Type of Sealing	Without	Not sealed
Cage	MP	Solid brass cage, ball guided
Tolerance class	P5	Class5 (P5), better than P6
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°
Bearing with matched conditions for fitting in pairs	UL	Bearing set with light preload
Lubricant	Without	Bearing not greased

## Main Dimensions &amp; Performance Data

d	380 mm	Bore diameter
D	520 mm	Outside diameter
B	65 mm	Width
C <sub>r</sub>	400.000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	720.000 N	Basic static load rating, radial
C <sub>ur</sub>	21.100 N	Fatigue load limit, radial
n <sub>G</sub>	1.760 1/min	Limiting speed
n <sub>gr</sub>	1.110 1/min	Reference speed
≈m	41,7 kg	Weight





### Mounting dimensions

$d_{a \min}$	394,6 mm	Minimum diameter of shaft shoulder
$D_{a \max}$	505,4 mm	Maximum diameter of housing shoulder
$D_{b \max}$	513 mm	Maximum diameter of housing shoulder
$r_{a \max}$	3 mm	Maximum fillet radius of shaft
$r_{a1 \max}$	1,5 mm	Maximum fillet radius of housing

### Dimensions

$r_{\min}$	4 mm	Minimum chamfer dimension
$r_{1 \min}$	1,5 mm	Minimum chamfer dimension
$D_1$	468 mm	Shoulder diameter on outer ring wide side face
$d_1$	432 mm	Shoulder diameter on inner ring wide side face
$a$	162,4 mm	Distance between the apexes of the pressure cones
$\alpha$	30 °	Contact angle

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.

### Additional information

$V_{\max}$	-16 $\mu\text{m}$	Preload per set max.
Tol (+)	18 $\mu\text{m}$	Tolerance for axial clearance or preload per set
$F_{V \max}$	3.077 N	Preload force



### Characteristics

---

-  Radial load
-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Large bearing