

**FAG****7238-B-MP-UO**

Angular contact ball bearing

Angular contact ball bearing 72..-B-MP, single row, solid brass cage



Technical information



Your current product variant

Design variant	B	B
Type of Sealing	Without	Not sealed
Cage	MP	Solid brass cage, ball guided
Tolerance class	PN	Normal (PN)
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°
Bearing with matched conditions for fitting in pairs	UO	Bearing set clearance-free in O or X arrangement
Lubricant	Without	Bearing not greased

Main Dimensions & Performance Data

d	190 mm	Bore diameter
D	340 mm	Outside diameter
B	55 mm	Width
C _r	300.000 N	Basic dynamic load rating, radial
C _{0r}	425.000 N	Basic static load rating, radial
C _{ur}	13.600 N	Fatigue load limit, radial
n _G	2.950 1/min	Limiting speed
n _{gr}	2.140 1/min	Reference speed
≈m	21,8 kg	Weight



Mounting dimensions

$d_{a \min}$	207 mm	Minimum diameter of shaft shoulder
$D_{a \max}$	323 mm	Maximum diameter of housing shoulder
$D_{b \max}$	331 mm	Maximum diameter of housing shoulder
$r_{a \max}$	3 mm	Maximum fillet radius of shaft
$r_{a1 \max}$	1,5 mm	Maximum fillet radius of housing

Dimensions

r_{\min}	4 mm	Minimum chamfer dimension
$r_{1 \min}$	1,5 mm	Minimum chamfer dimension
D_1	281 mm	Shoulder diameter on outer ring wide side face
d_1	250 mm	Shoulder diameter on inner ring wide side face
a	138,7 mm	Distance between the apexes of the pressure cones
α	40 °	Contact angle

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	200 °C	Operating temperature max.

Additional information

A_{\min}	0 μm	Axial clearance per set min.
Tol (+)	16 μm	Tolerance for axial clearance or preload per set



Characteristics

-  Radial load
-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Large bearing