

**FAG****7260-B-MP-UA**

Angular contact ball bearing

Angular contact ball bearing 72..-B-MP, single row, solid brass cage



Technical information



Your current product variant

| | | |
|--|---------|---|
| Design variant | B | B |
| Type of Sealing | Without | Not sealed |
| Cage | MP | Solid brass cage, ball guided |
| Tolerance class | PN | Normal (PN) |
| Dimensional / heat stabilization | S1 | Rings dimensional stabilized up to 200° |
| Bearing with matched conditions for fitting in pairs | UA | Bearing set with small axial internal clearance |
| Lubricant | Without | Bearing not greased |

Main Dimensions & Performance Data

| | | |
|-----------------|-------------|-----------------------------------|
| d | 300 mm | Bore diameter |
| D | 540 mm | Outside diameter |
| B | 85 mm | Width |
| C _r | 560.000 N | Basic dynamic load rating, radial |
| C _{0r} | 1.050.000 N | Basic static load rating, radial |
| C _{ur} | 27.000 N | Fatigue load limit, radial |
| n _G | 1.790 1/min | Limiting speed |
| n _{gr} | 1.210 1/min | Reference speed |
| ≈m | 86,4 kg | Weight |



Mounting dimensions

| | | |
|---------------|--------|--------------------------------------|
| $d_{a \min}$ | 320 mm | Minimum diameter of shaft shoulder |
| $D_{a \max}$ | 520 mm | Maximum diameter of housing shoulder |
| $D_{b \max}$ | 529 mm | Maximum diameter of housing shoulder |
| $r_{a \max}$ | 4 mm | Maximum fillet radius of shaft |
| $r_{a1 \max}$ | 2 mm | Maximum fillet radius of housing |

Dimensions

| | | |
|--------------|-----------|---|
| r_{\min} | 5 mm | Minimum chamfer dimension |
| $r_{1 \min}$ | 2 mm | Minimum chamfer dimension |
| D_1 | 445,65 mm | Shoulder diameter on outer ring wide side face |
| d_1 | 399,45 mm | Shoulder diameter on inner ring wide side face |
| a | 218,7 mm | Distance between the apexes of the pressure cones |
| α | 40 ° | Contact angle |

Temperature range

| | | |
|------------|--------|----------------------------|
| T_{\min} | -30 °C | Operating temperature min. |
| T_{\max} | 200 °C | Operating temperature max. |

Additional information

| | | |
|------------|-------------------|--|
| A_{\min} | 146 μm | Axial clearance per set min. |
| Tol (+) | 16 μm | Tolerance for axial clearance or preload per set |



Characteristics

-  Radial load
-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Large bearing