

**FAG****X-life****7207-B-XL-2RS-TVP-UA**

Angular contact ball bearing

Angular contact ball bearing 72..-B-XL-2RS-TVP, single row, X-life, seals, plastic cage

## Technical information

**Your current product variant**

Design variant	B	B
Type of Sealing	2RS	Contact seal on both sides
Cage	TVP	Solid cage made of glass-fiber reinforced polyamid PA66
Tolerance class	P6	Class6 (P6), better than PN
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Bearing with matched conditions for fitting in pairs	UA	Bearing set with small axial internal clearance
Lubricant	GA13	Ball bearing and insert bearing grease

**Main Dimensions & Performance Data**

d	35 mm	Bore diameter
D	72 mm	Outside diameter
B	17 mm	Width
C <sub>r</sub>	30.000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	19.000 N	Basic static load rating, radial
C <sub>ur</sub>	1.320 N	Fatigue load limit, radial
n <sub>G</sub>	5.600 1/min	Limiting speed
m	0,275 kg	Weight



### Mounting dimensions

$d_{a \min}$	42 mm	Minimum diameter of shaft shoulder
$D_{a \max}$	65 mm	Maximum diameter of housing shoulder
$D_{b \max}$	67,8 mm	Maximum diameter of housing shoulder
$r_{a \max}$	1 mm	Maximum fillet radius of shaft
$r_{a1 \max}$	0,6 mm	Maximum fillet radius of housing

### Dimensions

$r_{\min}$	1,1 mm	Minimum chamfer dimension
$r_{1 \min}$	0,6 mm	Minimum chamfer dimension
$D_1$	57,64 mm	Shoulder diameter on outer ring wide side face
$D_2$	60,22 mm	Caliber diameter on outer ring wide side face
$D_3$	66,54 mm	Caliber diameter on outer ring small side face
$d_1$	50,17 mm	Shoulder diameter on inner ring wide side face
$d_2$	45,76 mm	Caliber diameter on inner ring wide side face
$a$	30,9 mm	Distance between the apexes of the pressure cones
$\alpha$	40 °	Contact angle

### Temperature range

$T_{\min}$	-20 °C	Operating temperature min.
$T_{\max}$	100 °C	Operating temperature max.

### Additional information

$A_{\min}$	40 $\mu\text{m}$	Axial clearance per set min.
Tol (+)	8 $\mu\text{m}$	Tolerance for axial clearance or preload per set



### Characteristics

---



Radial load



Axial load in one direction



Lifetime lubrication, freedom from maintenance



Grease Lubrication



Sealed on both sides