

**FAG****7200-B-XL-JP**

Angular contact ball bearing

Angular contact ball bearing 72..-B-XL-JP,
single row, X-life, steel sheet metal cage**X-life**

Technical information



Your current product variant

| | | |
|----------------------------------|---------|---|
| Design variant | B | B |
| Type of Seal | Without | Not sealed |
| Cage | JP | Steel sheet metal |
| Tolerance class | P6 | Class6 (P6), better than PN |
| Dimensional / heat stabilization | S0 | Rings dimensional stabilized up to 150° |
| Lubricant | Without | Bearing not greased |

Main Dimensions & Performance Data

| | | |
|-----------------|--------------|-----------------------------------|
| d | 10 mm | Bore diameter |
| D | 30 mm | Outside diameter |
| B | 9 mm | Width |
| C _r | 5.600 N | Basic dynamic load rating, radial |
| C _{0r} | 2.600 N | Basic static load rating, radial |
| C _{ur} | 179 N | Fatigue load limit, radial |
| n _G | 37.500 1/min | Limiting speed |
| n _{gr} | 22.600 1/min | Reference speed |
| m | 0,033 kg | Weight |



Mounting dimensions

| | | |
|---------------|---------|--------------------------------------|
| $d_{a \min}$ | 14,2 mm | Minimum diameter of shaft shoulder |
| $D_{a \max}$ | 25,8 mm | Maximum diameter of housing shoulder |
| $D_{b \max}$ | 27,6 mm | Maximum diameter of housing shoulder |
| $r_{a \max}$ | 0,6 mm | Maximum fillet radius of shaft |
| $r_{a1 \max}$ | 0,3 mm | Maximum fillet radius of housing |

Dimensions

| | | |
|--------------|----------|---|
| r_{\min} | 0,6 mm | Minimum chamfer dimension |
| $r_{1 \min}$ | 0,3 mm | Minimum chamfer dimension |
| D_1 | 22,03 mm | Shoulder diameter on outer ring wide side face |
| d_1 | 18,26 mm | Shoulder diameter on inner ring wide side face |
| a | 12,9 mm | Distance between the apexes of the pressure cones |
| α | 40 ° | Contact angle |

Temperature range

| | | |
|------------|--------|----------------------------|
| T_{\min} | -30 °C | Operating temperature min. |
| T_{\max} | 150 °C | Operating temperature max. |

Characteristics

| | |
|---|-----------------------------|
|  | Radial load |
|  | Axial load in one direction |
|  | Grease Lubrication |
|  | Oil Lubrication |
|  | Not sealed |