

**FAG****7201-B-XL-JP-UO**

Angular contact ball bearing

Angular contact ball bearing 72..-B-XL-JP,
single row, X-life, steel sheet metal cage**X-life**

Technical information

**Your current product variant**

Design variant	B	B
Sealing	Without	Not sealed
Cage	JP	Steel sheet metal
Tolerance class	P6	Class6 (P6), better than PN
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Bearing with matched conditions for fitting in pairs	UO	Bearing set clearance-free in O or X arrangement
Lubricant	Without	Bearing not greased

Main Dimensions & Performance Data

d	12 mm	Bore diameter
D	32 mm	Outside diameter
B	10 mm	Width
C _r	7.900 N	Basic dynamic load rating, radial
C _{0r}	3.550 N	Basic static load rating, radial
C _{ur}	248 N	Fatigue load limit, radial
n _G	33.000 1/min	Limiting speed
n _{gr}	21.100 1/min	Reference speed
≈m	0,042 kg	Weight



Mounting dimensions

$d_{a \min}$	16,2 mm	Minimum diameter of shaft shoulder
$D_{a \max}$	27,8 mm	Maximum diameter of housing shoulder
$D_{b \max}$	29,6 mm	Maximum diameter of housing shoulder
$r_{a \max}$	0,6 mm	Maximum fillet radius of shaft
$r_{a1 \max}$	0,3 mm	Maximum fillet radius of housing

Dimensions

r_{\min}	0,6 mm	Minimum chamfer dimension
$r_{1 \min}$	0,3 mm	Minimum chamfer dimension
D_1	24,63 mm	Shoulder diameter on outer ring wide side face
d_1	19,76 mm	Shoulder diameter on inner ring wide side face
a	14,2 mm	Distance between the apexes of the pressure cones
α	40 °	Contact angle

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	150 °C	Operating temperature max.

Additional information

A_{\min}	0 μm	Axial clearance per set min.
Tol (+)	8 μm	Tolerance for axial clearance or preload per set

Characteristics

	Radial load
	Axial load in one direction
	Grease Lubrication
	Oil Lubrication
	Not sealed