

**FAG****7206-B-XL-JP**

Angular contact ball bearing

Angular contact ball bearing 72..-B-XL-JP,  
single row, X-life, steel sheet metal cage**X-life**

## Technical information



## Your current product variant

Design variant	B	B
Type of Seal	Without	Not sealed
Cage	JP	Steel sheet metal
Tolerance class	P6	Class6 (P6), better than PN
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Lubricant	Without	Bearing not greased

## Main Dimensions &amp; Performance Data

d	30 mm	Bore diameter
D	62 mm	Outside diameter
B	16 mm	Width
$C_r$	23.100 N	Basic dynamic load rating, radial
$C_{0r}$	14.100 N	Basic static load rating, radial
$C_{ur}$	980 N	Fatigue load limit, radial
$n_G$	15.800 1/min	Limiting speed
$n_{gr}$	11.200 1/min	Reference speed
$m$	0,205 kg	Weight



### Mounting dimensions

$d_{a \min}$	35,6 mm	Minimum diameter of shaft shoulder
$D_{a \max}$	56,4 mm	Maximum diameter of housing shoulder
$D_{b \max}$	57,8 mm	Maximum diameter of housing shoulder
$r_{a \max}$	1 mm	Maximum fillet radius of shaft
$r_{a1 \max}$	0,6 mm	Maximum fillet radius of housing

### Dimensions

$r_{\min}$	1 mm	Minimum chamfer dimension
$r_{1 \min}$	0,6 mm	Minimum chamfer dimension
$D_1$	49,52 mm	Shoulder diameter on outer ring wide side face
$d_1$	43,2 mm	Shoulder diameter on inner ring wide side face
$a$	27,3 mm	Distance between the apexes of the pressure cones
$\alpha$	40 °	Contact angle

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	150 °C	Operating temperature max.

### Characteristics

	Radial load
	Axial load in one direction
	Grease Lubrication
	Oil Lubrication
	Not sealed