

**FAG****7208-B-XL-JP-UA**

Angular contact ball bearing

Angular contact ball bearing 72..-B-XL-JP, single row, X-life, steel sheet metal cage

X-life

Technical information



Your current product variant

Design variant	B	B
Sealing	Without	Not sealed
Cage	JP	Steel sheet metal
Tolerance class	P6	Class 6 (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Bearing with matched conditions for fitting in pairs	UA	Bearing set with small axial internal clearance
Lubricant	Without	Bearing not greased

Main Dimensions & Performance Data

d	40 mm	Bore diameter
D	80 mm	Outside diameter
B	18 mm	Width
C_r	36.000 N	Basic dynamic load rating, radial
C_{0r}	23.500 N	Basic static load rating, radial
C_{ur}	1.630 N	Fatigue load limit, radial
n_G	11.900 1/min	Limiting speed
n_{gr}	8.600 1/min	Reference speed
m	0,386 kg	Weight



Mounting dimensions

$d_{a \min}$	47 mm	Minimum diameter of shaft shoulder
$D_{a \max}$	73 mm	Maximum diameter of housing shoulder
$D_{b \max}$	75,8 mm	Maximum diameter of housing shoulder
$r_{a \max}$	1 mm	Maximum fillet radius of shaft
$r_{a1 \max}$	0,6 mm	Maximum fillet radius of housing

Dimensions

r_{\min}	1,1 mm	Minimum chamfer dimension
$r_{1 \min}$	0,6 mm	Minimum chamfer dimension
D_1	64,4 mm	Shoulder diameter on outer ring wide side face
d_1	56,42 mm	Shoulder diameter on inner ring wide side face
a	34,2 mm	Distance between the apexes of the pressure cones
α	40 °	Contact angle

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	150 °C	Operating temperature max.

Additional information

A_{\min}	40 μm	Axial clearance per set min.
Tol (+)	8 μm	Tolerance for axial clearance or preload per set

Characteristics

	Radial load
	Axial load in one direction
	Grease Lubrication
	Oil Lubrication
	Not sealed