



## Technical information



### Your current product variant

Design variant	B	B
Type of Seal	Without	Not sealed
Cage	TVP	Solid cage made of glass-fiber reinforced polyamid PA66
Tolerance class	P5	Class5 (P5), better than P6
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Bearing with matched conditions for fitting in pairs	UL	Bearing set with light preload
Lubricant	Without	Bearing not greased

### Main Dimensions & Performance Data

d	12 mm	Bore diameter
D	32 mm	Outside diameter
B	10 mm	Width
C <sub>r</sub>	7.900 N	Basic dynamic load rating, radial
C <sub>0r</sub>	3.550 N	Basic static load rating, radial
C <sub>ur</sub>	248 N	Fatigue load limit, radial
n <sub>G</sub>	33.000 1/min	Limiting speed
n <sub>gr</sub>	21.100 1/min	Reference speed
≈m	0,035 kg	Weight



### Mounting dimensions

$d_{a \min}$	16,2 mm	Minimum diameter of shaft shoulder
$D_{a \max}$	27,8 mm	Maximum diameter of housing shoulder
$D_{b \max}$	29,6 mm	Maximum diameter of housing shoulder
$r_{a \max}$	0,6 mm	Maximum fillet radius of shaft
$r_{a1 \max}$	0,3 mm	Maximum fillet radius of housing

### Dimensions

$r_{\min}$	0,6 mm	Minimum chamfer dimension
$r_{1 \min}$	0,3 mm	Minimum chamfer dimension
$D_1$	24,63 mm	Shoulder diameter on outer ring wide side face
$d_1$	19,76 mm	Shoulder diameter on inner ring wide side face
$a$	14,2 mm	Distance between the apexes of the pressure cones
$\alpha$	40 °	Contact angle

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

### Additional information

$V_{\max}$	-4 $\mu\text{m}$	Preload per set max.
Tol (+)	6 $\mu\text{m}$	Tolerance for axial clearance or preload per set
$F_{V \max}$	53 N	Preload force



### Characteristics

---

-  Radial load
-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed