



FAG

7212-B-XL-TVP [↗](#)

Angular contact ball bearing

Angular contact ball bearing 72..-B-XL-TVP, single row, X-life, plastic cage

X-life

Technical information



Your current product variant

| | | |
|----------------------------------|---------|---|
| Design variant | B | B |
| Type of Seal | Without | Not sealed |
| Cage | TVP | Solid cage made of glass-fiber reinforced polyamid PA66 |
| Tolerance class | P6 | Class6 (P6), better than PN |
| Dimensional / heat stabilization | S0 | Rings dimensional stabilized up to 150° |
| Lubricant | Without | Bearing not greased |

Main Dimensions & Performance Data

| | | |
|-----------------|-------------|-----------------------------------|
| d | 60 mm | Bore diameter |
| D | 110 mm | Outside diameter |
| B | 22 mm | Width |
| C _r | 62.000 N | Basic dynamic load rating, radial |
| C _{0r} | 45.000 N | Basic static load rating, radial |
| C _{ur} | 3.150 N | Fatigue load limit, radial |
| n _G | 8.300 1/min | Limiting speed |
| n _{gr} | 6.200 1/min | Reference speed |
| ≈m | 0,78 kg | Weight |



Mounting dimensions

| | | |
|---------------|----------|--------------------------------------|
| $d_{a \min}$ | 69 mm | Minimum diameter of shaft shoulder |
| $D_{a \max}$ | 101 mm | Maximum diameter of housing shoulder |
| $D_{b \max}$ | 104,4 mm | Maximum diameter of housing shoulder |
| $r_{a \max}$ | 1,5 mm | Maximum fillet radius of shaft |
| $r_{a1 \max}$ | 1 mm | Maximum fillet radius of housing |

Dimensions

| | | |
|--------------|----------|---|
| r_{\min} | 1,5 mm | Minimum chamfer dimension |
| $r_{1 \min}$ | 1 mm | Minimum chamfer dimension |
| D_1 | 90,84 mm | Shoulder diameter on outer ring wide side face |
| d_1 | 80,32 mm | Shoulder diameter on inner ring wide side face |
| a | 46,7 mm | Distance between the apexes of the pressure cones |
| α | 40 ° | Contact angle |

Temperature range

| | | |
|------------|--------|----------------------------|
| T_{\min} | -30 °C | Operating temperature min. |
| T_{\max} | 120 °C | Operating temperature max. |

Characteristics

-  Radial load
-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed