

**FAG****7328-B-MP**

Angular contact ball bearing

Angular contact ball bearing 73..-B-MP, single row, solid brass cage



## Technical information



## Your current product variant

Design variant	B	B
Type of Seal	Without	Not sealed
Cage	MP	Solid brass cage, ball guided
Tolerance class	PN	Normal (PN)
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°
Lubricant	Without	Bearing not greased

## Main Dimensions &amp; Performance Data

d	140 mm	Bore diameter
D	300 mm	Outside diameter
B	62 mm	Width
$C_r$	310.000 N	Basic dynamic load rating, radial
$C_{0r}$	375.000 N	Basic static load rating, radial
$C_{ur}$	13.100 N	Fatigue load limit, radial
$n_G$	3.350 1/min	Limiting speed
$n_{gr}$	2.400 1/min	Reference speed
$m$	21,3 kg	Weight



### Mounting dimensions

$d_{a \min}$	157 mm	Minimum diameter of shaft shoulder
$D_{a \max}$	283 mm	Maximum diameter of housing shoulder
$D_{b \max}$	291 mm	Maximum diameter of housing shoulder
$r_{a \max}$	3 mm	Maximum fillet radius of shaft
$r_{a1 \max}$	1,5 mm	Maximum fillet radius of housing

### Dimensions

$r_{\min}$	4 mm	Minimum chamfer dimension
$r_{1 \min}$	1,5 mm	Minimum chamfer dimension
$D_1$	239,5 mm	Shoulder diameter on outer ring wide side face
$d_1$	204,38 mm	Shoulder diameter on inner ring wide side face
$a$	123,3 mm	Distance between the apexes of the pressure cones
$\alpha$	40 °	Contact angle

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.

### Characteristics

-   $F_r$  Radial load
-   $F_a$  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed