

**FAG****7338-B-MP-UA**

Angular contact ball bearing

Angular contact ball bearing 73..-B-MP, single row, solid brass cage



## Technical information

**Your current product variant**

Design variant	B	B
Type of Seal	Without	Not sealed
Cage	MP	Solid brass cage, ball guided
Tolerance class	PN	Normal (PN)
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°
Bearing with matched conditions for fitting in pairs	UA	Bearing set with small axial internal clearance
Lubricant	Without	Bearing not greased

**Main Dimensions & Performance Data**

d	190 mm	Bore diameter
D	400 mm	Outside diameter
B	78 mm	Width
C <sub>r</sub>	440.000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	630.000 N	Basic static load rating, radial
C <sub>ur</sub>	19.200 N	Fatigue load limit, radial
n <sub>G</sub>	2.490 1/min	Limiting speed
n <sub>gr</sub>	1.680 1/min	Reference speed
≈m	47,9 kg	Weight



### Mounting dimensions

$d_{a \min}$	210 mm	Minimum diameter of shaft shoulder
$D_{a \max}$	380 mm	Maximum diameter of housing shoulder
$D_{b \max}$	389 mm	Maximum diameter of housing shoulder
$r_{a \max}$	4 mm	Maximum fillet radius of shaft
$r_{a1 \max}$	2 mm	Maximum fillet radius of housing

### Dimensions

$r_{\min}$	5 mm	Minimum chamfer dimension
$r_{1 \min}$	2 mm	Minimum chamfer dimension
$D_1$	318 mm	Shoulder diameter on outer ring wide side face
$d_1$	273 mm	Shoulder diameter on inner ring wide side face
$a$	162,8 mm	Distance between the apexes of the pressure cones
$\alpha$	40 °	Contact angle

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.

### Additional information

$A_{\min}$	80 $\mu\text{m}$	Axial clearance per set min.
Tol (+)	16 $\mu\text{m}$	Tolerance for axial clearance or preload per set



### Characteristics

---

-  Radial load
-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Large bearing