

**FAG****7340-B-MP-P5-UL**

Angular contact ball bearing

Angular contact ball bearing 73..-B-MP, single row, solid brass cage



## Technical information



## Your current product variant

Design variant	B	B
Sealing	Without	Not sealed
Cage	MP	Solid brass cage, ball guided
Tolerance class	P5	Class5 (P5), better than P6
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°
Bearing with matched conditions for fitting in pairs	UL	Bearing set with light preload
Lubricant	Without	Bearing not greased

## Main Dimensions &amp; Performance Data

d	200 mm	Bore diameter
D	420 mm	Outside diameter
B	80 mm	Width
$C_r$	475.000 N	Basic dynamic load rating, radial
$C_{0r}$	710.000 N	Basic static load rating, radial
$C_{ur}$	21.000 N	Fatigue load limit, radial
$n_G$	2.360 1/min	Limiting speed
$n_{gr}$	1.560 1/min	Reference speed
$\approx m$	54,4 kg	Weight



### Mounting dimensions

$d_{a \min}$	220 mm	Minimum diameter of shaft shoulder
$D_{a \max}$	400 mm	Maximum diameter of housing shoulder
$D_{b \max}$	409 mm	Maximum diameter of housing shoulder
$r_{a \max}$	4 mm	Maximum fillet radius of shaft
$r_{a1 \max}$	2 mm	Maximum fillet radius of housing

### Dimensions

$r_{\min}$	5 mm	Minimum chamfer dimension
$r_{1 \min}$	2 mm	Minimum chamfer dimension
$D_1$	336,6 mm	Shoulder diameter on outer ring wide side face
$d_1$	288,85 mm	Shoulder diameter on inner ring wide side face
$a$	170,1 mm	Distance between the apexes of the pressure cones
$\alpha$	40 °	Contact angle

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.

### Additional information

$V_{\max}$	-20 $\mu\text{m}$	Preload per set max.
Tol (+)	14 $\mu\text{m}$	Tolerance for axial clearance or preload per set
$F_{V \max}$	3.577 N	Preload force



### Characteristics

---

-  Radial load
-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Large bearing