

**FAG****7356-B-MP-UA**

Angular contact ball bearing

Angular contact ball bearing 73..-B-MP, single row, solid brass cage



## Technical information



## Your current product variant

Design variant	B	B
Sealing	Without	Not sealed
Cage	MP	Solid brass cage, ball guided
Tolerance class	PN	Normal (PN)
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°
Bearing with matched conditions for fitting in pairs	UA	Bearing set with small axial internal clearance
Lubricant	Without	Bearing not greased

## Main Dimensions &amp; Performance Data

d	280 mm	Bore diameter
D	580 mm	Outside diameter
B	108 mm	Width
C <sub>r</sub>	730.000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	1.350.000 N	Basic static load rating, radial
C <sub>ur</sub>	34.000 N	Fatigue load limit, radial
n <sub>G</sub>	1.670 1/min	Limiting speed
n <sub>gr</sub>	1.040 1/min	Reference speed
≈m	142 kg	Weight



### Mounting dimensions

$d_{a \min}$	306 mm	Minimum diameter of shaft shoulder
$D_{a \max}$	554 mm	Maximum diameter of housing shoulder
$D_{b \max}$	566 mm	Maximum diameter of housing shoulder
$r_{a \max}$	5 mm	Maximum fillet radius of shaft
$r_{a1 \max}$	2,5 mm	Maximum fillet radius of housing

### Dimensions

$r_{\min}$	6 mm	Minimum chamfer dimension
$r_{1 \min}$	3 mm	Minimum chamfer dimension
$D_1$	464,45 mm	Shoulder diameter on outer ring wide side face
$d_1$	402,5 mm	Shoulder diameter on inner ring wide side face
$a$	234,4 mm	Distance between the apexes of the pressure cones
$\alpha$	40 °	Contact angle

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.

### Additional information

$A_{\min}$	130 $\mu\text{m}$	Axial clearance per set min.
Tol (+)	16 $\mu\text{m}$	Tolerance for axial clearance or preload per set



### Characteristics

---

-  Radial load
-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Large bearing