

**FAG****X-life****7308-B-XL-MP-P5-UL**

Angular contact ball bearing

Angular contact ball bearing 73..-B-XL-MP,  
single row, X-life, solid brass cage

## Technical information

**Your current product variant**

Design variant	B	B
Sealing	Without	Not sealed
Cage	MP	Solid brass cage, ball guided
Tolerance class	P5	Class 5 (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Bearing with matched conditions for fitting in pairs	UL	Bearing set with light preload
Lubricant	Without	Bearing not greased

**Main Dimensions & Performance Data**

d	40 mm	Bore diameter
D	90 mm	Outside diameter
B	23 mm	Width
$C_r$	57.000 N	Basic dynamic load rating, radial
$C_{0r}$	34.500 N	Basic static load rating, radial
$C_{ur}$	2.390 N	Fatigue load limit, radial
$n_G$	13.500 1/min	Limiting speed
$n_{gr}$	7.100 1/min	Reference speed
$\approx m$	0,68 kg	Weight



### Mounting dimensions

$d_{a \min}$	49 mm	Minimum diameter of shaft shoulder
$D_{a \max}$	81 mm	Maximum diameter of housing shoulder
$D_{b \max}$	84,4 mm	Maximum diameter of housing shoulder
$r_{a \max}$	1,5 mm	Maximum fillet radius of shaft
$r_{a1 \max}$	1 mm	Maximum fillet radius of housing

### Dimensions

$r_{\min}$	1,5 mm	Minimum chamfer dimension
$r_{1 \min}$	1 mm	Minimum chamfer dimension
$D_1$	71,28 mm	Shoulder diameter on outer ring wide side face
$d_1$	59,99 mm	Shoulder diameter on inner ring wide side face
$a$	38,8 mm	Distance between the apexes of the pressure cones
$\alpha$	40 °	Contact angle

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	150 °C	Operating temperature max.

### Additional information

$V_{\max}$	-8 $\mu\text{m}$	Preload per set max.
Tol (+)	6 $\mu\text{m}$	Tolerance for axial clearance or preload per set
$F_V \max$	385 N	Preload force



### Characteristics

---

-  Radial load
-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed