


**FAG****7311-B-XL-MP**

Angular contact ball bearing

Angular contact ball bearing 73..-B-XL-MP,  
single row, X-life, solid brass cage**X-life**

## Technical information

**Your current product variant**

Design variant	B	B
Type of Seal	Without	Not sealed
Cage	MP	Solid brass cage, ball guided
Tolerance class	P6	Class6 (P6), better than PN
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Lubricant	Without	Bearing not greased

**Main Dimensions & Performance Data**

d	55 mm	Bore diameter
D	120 mm	Outside diameter
B	29 mm	Width
$C_r$	91.000 N	Basic dynamic load rating, radial
$C_{0r}$	61.000 N	Basic static load rating, radial
$C_{ur}$	4.250 N	Fatigue load limit, radial
$n_G$	10.000 1/min	Limiting speed
$n_{gr}$	5.600 1/min	Reference speed
$m$	1,53 kg	Weight



### Mounting dimensions

$d_{a \min}$	66 mm	Minimum diameter of shaft shoulder
$D_{a \max}$	109 mm	Maximum diameter of housing shoulder
$D_{b \max}$	114,4 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2 mm	Maximum fillet radius of shaft
$r_{a1 \max}$	1 mm	Maximum fillet radius of housing

### Dimensions

$r_{\min}$	2 mm	Minimum chamfer dimension
$r_{1 \min}$	1 mm	Minimum chamfer dimension
$D_1$	95,3 mm	Shoulder diameter on outer ring wide side face
$d_1$	80,3 mm	Shoulder diameter on inner ring wide side face
$a$	51,2 mm	Distance between the apexes of the pressure cones
$\alpha$	40 °	Contact angle

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	150 °C	Operating temperature max.

### Characteristics

-  Radial load
-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed