



FAG

**7307-B-XL-TVP-UL** [↗](#)

Angular contact ball bearing

Angular contact ball bearing 73.-B-XL-TVP, single row, X-life, plastic cage

X-life

## Technical information



## Your current product variant

Design variant	B	B
Type of Seal	Without	Not sealed
Cage	TVP	Solid cage made of glass-fiber reinforced polyamid PA66
Tolerance class	P6	Class6 (P6), better than PN
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Bearing with matched conditions for fitting in pairs	UL	Bearing set with light preload
Lubricant	Without	Bearing not greased

## Main Dimensions &amp; Performance Data

d	35 mm	Bore diameter
D	80 mm	Outside diameter
B	21 mm	Width
C <sub>r</sub>	45.500 N	Basic dynamic load rating, radial
C <sub>0r</sub>	27.500 N	Basic static load rating, radial
C <sub>ur</sub>	1.910 N	Fatigue load limit, radial
n <sub>G</sub>	11.900 1/min	Limiting speed
n <sub>gr</sub>	7.900 1/min	Reference speed
≈m	0,446 kg	Weight



### Mounting dimensions

$d_{a \min}$	44 mm	Minimum diameter of shaft shoulder
$D_{a \max}$	71 mm	Maximum diameter of housing shoulder
$D_{b \max}$	74,4 mm	Maximum diameter of housing shoulder
$r_{a \max}$	1,5 mm	Maximum fillet radius of shaft
$r_{a1 \max}$	1 mm	Maximum fillet radius of housing

### Dimensions

$r_{\min}$	1,5 mm	Minimum chamfer dimension
$r_{1 \min}$	1 mm	Minimum chamfer dimension
$D_1$	63,02 mm	Shoulder diameter on outer ring wide side face
$d_1$	53,12 mm	Shoulder diameter on inner ring wide side face
$a$	34,6 mm	Distance between the apexes of the pressure cones
$\alpha$	40 °	Contact angle

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

### Additional information

$V_{\max}$	-8 $\mu\text{m}$	Preload per set max.
Tol (+)	8 $\mu\text{m}$	Tolerance for axial clearance or preload per set
$F_{V \max}$	300 N	Preload force



### Characteristics

---

-  Radial load
-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed