


Technical information



Your current product variant

| | | |
|----------------------------------|---------|---|
| Design variant | B | B |
| Sealing | Without | Not sealed |
| Cage | TVP | Solid cage made of glass-fiber reinforced polyamid PA66 |
| Tolerance class | PN | Normal (ISO 492:2023) |
| Dimensional / heat stabilization | S0 | Rings dimensional stabilized up to 150° |
| Lubricant | Without | Bearing not greased |

Main Dimensions & Performance Data

| | | |
|-----------------|-------------|-----------------------------------|
| d | 110 mm | Bore diameter |
| D | 240 mm | Outside diameter |
| B | 50 mm | Width |
| C _r | 250.000 N | Basic dynamic load rating, radial |
| C _{0r} | 245.000 N | Basic static load rating, radial |
| C _{ur} | 12.800 N | Fatigue load limit, radial |
| n _G | 3.650 1/min | Limiting speed |
| n _{gr} | 3.150 1/min | Reference speed |
| ≈m | 9,74 kg | Weight |



Mounting dimensions

| | | |
|---------------|--------|--------------------------------------|
| $d_{a \min}$ | 124 mm | Minimum diameter of shaft shoulder |
| $D_{a \max}$ | 226 mm | Maximum diameter of housing shoulder |
| $D_{b \max}$ | 233 mm | Maximum diameter of housing shoulder |
| $r_{a \max}$ | 2,5 mm | Maximum fillet radius of shaft |
| $r_{a1 \max}$ | 1 mm | Maximum fillet radius of housing |

Dimensions

| | | |
|--------------|-----------|---|
| r_{\min} | 3 mm | Minimum chamfer dimension |
| $r_{1 \min}$ | 1,1 mm | Minimum chamfer dimension |
| D_1 | 190,9 mm | Shoulder diameter on outer ring wide side face |
| d_1 | 162,34 mm | Shoulder diameter on inner ring wide side face |
| a | 98,4 mm | Distance between the apexes of the pressure cones |
| α | 40 ° | Contact angle |

Temperature range

| | | |
|------------|--------|----------------------------|
| T_{\min} | -30 °C | Operating temperature min. |
| T_{\max} | 120 °C | Operating temperature max. |

Characteristics

-  F_r Radial load
-  F_a Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed