

**FAG****7408-B-XL-MP-UO**

Angular contact ball bearing

Angular contact ball bearing 74..-B-XL-MP,
single row, X-life, solid brass cage**X-life**

Technical information



Your current product variant

| | | |
|--|---------|--|
| Design variant | B | B |
| Type of Sealing | Without | Not sealed |
| Cage | MP | Solid brass cage, ball guided |
| Tolerance class | PN | Normal (PN) |
| Dimensional / heat stabilization | S0 | Rings dimensional stabilized up to 150° |
| Bearing with matched conditions for fitting in pairs | UO | Bearing set clearance-free in O or X arrangement |
| Lubricant | Without | Bearing not greased |

Main Dimensions & Performance Data

| | | |
|-----------------|--------------|-----------------------------------|
| d | 40 mm | Bore diameter |
| D | 110 mm | Outside diameter |
| B | 27 mm | Width |
| C _r | 75.000 N | Basic dynamic load rating, radial |
| C _{0r} | 50.000 N | Basic static load rating, radial |
| C _{ur} | 3.500 N | Fatigue load limit, radial |
| n _G | 10.900 1/min | Limiting speed |
| n _{gr} | 5.000 1/min | Reference speed |
| m | 1,364 kg | Weight |



Mounting dimensions

| | | |
|---------------|----------|--------------------------------------|
| $d_{a \min}$ | 53 mm | Minimum diameter of shaft shoulder |
| $D_{a \max}$ | 97 mm | Maximum diameter of housing shoulder |
| $D_{b \max}$ | 104,4 mm | Maximum diameter of housing shoulder |
| $r_{a \max}$ | 2 mm | Maximum fillet radius of shaft |
| $r_{a1 \max}$ | 1 mm | Maximum fillet radius of housing |

Dimensions

| | | |
|--------------|---------|---|
| r_{\min} | 2 mm | Minimum chamfer dimension |
| $r_{1 \min}$ | 1 mm | Minimum chamfer dimension |
| D_1 | 87,6 mm | Shoulder diameter on outer ring wide side face |
| d_1 | 73,1 mm | Shoulder diameter on inner ring wide side face |
| a | 47,1 mm | Distance between the apexes of the pressure cones |
| α | 40 ° | Contact angle |

Temperature range

| | | |
|------------|--------|----------------------------|
| T_{\min} | -30 °C | Operating temperature min. |
| T_{\max} | 150 °C | Operating temperature max. |

Additional information

| | | |
|------------|------------------|--|
| A_{\min} | 0 μm | Axial clearance per set min. |
| Tol (+) | 12 μm | Tolerance for axial clearance or preload per set |

Characteristics

| | | |
|---|-------|-----------------------------|
|  | F_r | Radial load |
|  | F_a | Axial load in one direction |
|  | | Grease Lubrication |
|  | | Oil Lubrication |
|  | | Not sealed |