

**FAG****X-life****7411-B-XL-MP**

Angular contact ball bearing

Angular contact ball bearing 74..-B-XL-MP,  
single row, X-life, solid brass cage

## Technical information

**Your current product variant**

Design variant	B	B
Type of Seal	Without	Not sealed
Cage	MP	Solid brass cage, ball guided
Tolerance class	PN	Normal (PN)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Lubricant	Without	Bearing not greased

**Main Dimensions & Performance Data**

d	55 mm	Bore diameter
D	140 mm	Outside diameter
B	33 mm	Width
C <sub>r</sub>	110.000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	82.000 N	Basic static load rating, radial
C <sub>ur</sub>	5.600 N	Fatigue load limit, radial
n <sub>G</sub>	8.400 1/min	Limiting speed
n <sub>gr</sub>	4.150 1/min	Reference speed
m	2,642 kg	Weight



### Mounting dimensions

$d_{a \min}$	69 mm	Minimum diameter of shaft shoulder
$D_{a \max}$	126 mm	Maximum diameter of housing shoulder
$D_{b \max}$	131 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2,1 mm	Maximum fillet radius of shaft
$r_{a1 \max}$	1 mm	Maximum fillet radius of housing

### Dimensions

$r_{\min}$	2,1 mm	Minimum chamfer dimension
$r_{1 \min}$	1,1 mm	Minimum chamfer dimension
$D_1$	111,52 mm	Shoulder diameter on outer ring wide side face
$d_1$	95,3 mm	Shoulder diameter on inner ring wide side face
$a$	59,5 mm	Distance between the apexes of the pressure cones
$\alpha$	40 °	Contact angle

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	150 °C	Operating temperature max.

### Characteristics

-  Radial load
-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed