

**FAG****X-life****7200-B-XL-2RS-TVP-L212**

Angular contact ball bearing

Angular contact ball bearing 72..-B-XL-2RS-TVP, single row, X-life, seals, plastic cage

Technical information

**Your current product variant**

Design variant	B	B
Sealing	2RS	Contact seal on both sides
Cage	TVP	Solid cage made of glass-fiber reinforced polyamid PA66
Tolerance class	P6	Class6 (P6), better than PN
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Lubricant	L212	Grease (L212/customer specific)

Main Dimensions & Performance Data

d	10 mm	Bore diameter
D	30 mm	Outside diameter
B	9 mm	Width
C_r	5.600 N	Basic dynamic load rating, radial
C_{0r}	2.600 N	Basic static load rating, radial
C_{ur}	179 N	Fatigue load limit, radial
n_G	16.100 1/min	Limiting speed
$\approx m$	0,033 kg	Weight



Mounting dimensions

$d_{a \min}$	14,2 mm	Minimum diameter of shaft shoulder
$D_{a \max}$	25,8 mm	Maximum diameter of housing shoulder
$D_{b \max}$	27,6 mm	Maximum diameter of housing shoulder
$r_{a \max}$	0,6 mm	Maximum fillet radius of shaft
$r_{a1 \max}$	0,3 mm	Maximum fillet radius of housing

Dimensions

r_{\min}	0,6 mm	Minimum chamfer dimension
$r_{1 \min}$	0,3 mm	Minimum chamfer dimension
D_1	22,03 mm	Shoulder diameter on outer ring wide side face
D_2	23,17 mm	Caliber diameter on outer ring wide side face
D_3	25,42 mm	Caliber diameter on outer ring small side face
d_1	18,26 mm	Shoulder diameter on inner ring wide side face
d_2	15,52 mm	Caliber diameter on inner ring wide side face
a	12,9 mm	Distance between the apexes of the pressure cones
α	40 °	Contact angle

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	100 °C	Operating temperature max.

Characteristics

	Radial load
	Axial load in one direction
	Lifetime lubrication, freedom from maintenance
	Grease Lubrication
	Sealed on both sides