



FAG

**7204-B-XL-TVP-L055-UM** [↗](#)

Angular contact ball bearing

Angular contact ball bearing 72.-B-XL-TVP, single row, X-life, plastic cage

X-life

## Technical information



## Your current product variant

Design variant	B	B
Type of Seal	Without	Not sealed
Cage	TVP	Solid cage made of glass-fiber reinforced polyamid PA66
Tolerance class	P6	Class 6 (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Bearing with matched conditions for fitting in pairs	UM	Bearing set with moderate preload
Lubricant	L055	Grease (L055/customer specific)

## Main Dimensions &amp; Performance Data

d	20 mm	Bore diameter
D	47 mm	Outside diameter
B	14 mm	Width
C <sub>r</sub>	14.900 N	Basic dynamic load rating, radial
C <sub>0r</sub>	7.800 N	Basic static load rating, radial
C <sub>ur</sub>	540 N	Fatigue load limit, radial
n <sub>G</sub>	21.600 1/min	Limiting speed
n <sub>gr</sub>	15.400 1/min	Reference speed
≈m	0,104 kg	Weight



### Mounting dimensions

$d_{a \min}$	25,6 mm	Minimum diameter of shaft shoulder
$D_{a \max}$	41,4 mm	Maximum diameter of housing shoulder
$D_{b \max}$	42,8 mm	Maximum diameter of housing shoulder
$r_{a \max}$	1 mm	Maximum fillet radius of shaft
$r_{a1 \max}$	0,6 mm	Maximum fillet radius of housing

### Dimensions

$r_{\min}$	1 mm	Minimum chamfer dimension
$r_{1 \min}$	0,6 mm	Minimum chamfer dimension
$D_1$	37,04 mm	Shoulder diameter on outer ring wide side face
$d_1$	30,54 mm	Shoulder diameter on inner ring wide side face
$a$	21,1 mm	Distance between the apexes of the pressure cones
$\alpha$	40 °	Contact angle

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

### Additional information

$V_{\max}$	-8 $\mu\text{m}$	Preload per set max.
Tol (+)	8 $\mu\text{m}$	Tolerance for axial clearance or preload per set
$F_{V \max}$	309 N	Preload force



### Characteristics

---

-  Radial load
-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed