


**FAG****7312-B-XL-2RS-JP-L431**

Angular contact ball bearing

Angular contact ball bearing 73..-B-XL-2RS-TVP, single row, X-life, seals, steel sheet metal cage

X-life

Technical information

**Your current product variant**

| | | |
|----------------------------------|------|---|
| Design variant | B | B |
| Sealing | 2RS | Contact seal on both sides |
| Cage | JP | Steel sheet metal |
| Tolerance class | PN | Normal (PN) |
| Dimensional / heat stabilization | S0 | Rings dimensional stabilized up to 150° |
| Lubricant | L431 | Grease (L431/customer specific) |

Main Dimensions & Performance Data

| | | |
|-------------|-------------|-----------------------------------|
| d | 60 mm | Bore diameter |
| D | 130 mm | Outside diameter |
| B | 31 mm | Width |
| C_r | 96.000 N | Basic dynamic load rating, radial |
| C_{0r} | 69.000 N | Basic static load rating, radial |
| C_{ur} | 4.750 N | Fatigue load limit, radial |
| n_G | 3.150 1/min | Limiting speed |
| $\approx m$ | 1,803 kg | Weight |



Mounting dimensions

| | | |
|---------------|--------|--------------------------------------|
| $d_{a \min}$ | 72 mm | Minimum diameter of shaft shoulder |
| $D_{a \max}$ | 118 mm | Maximum diameter of housing shoulder |
| $D_{b \max}$ | 123 mm | Maximum diameter of housing shoulder |
| $r_{a \max}$ | 2,1 mm | Maximum fillet radius of shaft |
| $r_{a1 \max}$ | 1 mm | Maximum fillet radius of housing |

Dimensions

| | | |
|--------------|-----------|---|
| r_{\min} | 2,1 mm | Minimum chamfer dimension |
| $r_{1 \min}$ | 1,1 mm | Minimum chamfer dimension |
| D_1 | 103,4 mm | Shoulder diameter on outer ring wide side face |
| D_2 | 106,86 mm | Caliber diameter on outer ring wide side face |
| D_3 | 119,68 mm | Caliber diameter on outer ring small side face |
| d_1 | 87,3 mm | Shoulder diameter on inner ring wide side face |
| d_2 | 83,1 mm | Caliber diameter on inner ring wide side face |
| a | 55,4 mm | Distance between the apexes of the pressure cones |
| α | 40 ° | Contact angle |

Temperature range

| | | |
|------------|--------|----------------------------|
| T_{\min} | -30 °C | Operating temperature min. |
| T_{\max} | 100 °C | Operating temperature max. |

Characteristics

| | |
|---|--|
|  | Radial load |
|  | Axial load in one direction |
|  | Lifetime lubrication, freedom from maintenance |
|  | Grease Lubrication |
|  | Sealed on both sides |