

**FAG****3210-BD-XL-C3**

Angular contact ball bearing

Angular contact ball bearing 32..-BD-XL,  
double row, X-life, steel sheet metal cage**X-life**

## Technical information



## Your current product variant

Design variant	B	Bearing without filling slot
Changed internal design	D	D
Sealing	Without	Not sealed
Cage	JH	Steel sheet metal
Tolerance class	P6	Class 6 (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	Without	Bearing not greased
Axial internal clearance	C3	Group 3 (C3), bigger than CN

## Main Dimensions &amp; Performance Data

d	50 mm	Bore diameter
D	90 mm	Outside diameter
B	30,2 mm	Width
C <sub>r</sub>	53.000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	44.000 N	Basic static load rating, radial
C <sub>ur</sub>	3.050 N	Fatigue load limit, radial
n <sub>G</sub>	7.800 1/min	Limiting speed
n <sub>gr</sub>	7.600 1/min	Reference speed
≈m	0,681 kg	Weight



### Mounting dimensions

$d_{a \min}$	57 mm	Minimum diameter shaft shoulder
$D_{a \max}$	83 mm	Maximum diameter of housing shoulder
$r_{a \max}$	1 mm	Maximum fillet radius

### Dimensions

$r_{\min}$	1,1 mm	Minimum chamfer dimension
$D_1$	80,1 mm	Shoulder diameter outer ring
$D_2$	82,91 mm	Caliber diameter outer ring
$d_1$	64,9 mm	Shoulder diameter inner ring
$d_2$	62,83 mm	Caliber diameter inner ring
$a$	53,2 mm	Distance between the apexes of the pressure cones
$\alpha$	30 °	Contact angle

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

### Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Grease Lubrication
	Oil Lubrication
	Not sealed