

**FAG****3211-BD-XL-2HRS-TVH**

Angular contact ball bearing

Angular contact ball bearing 32..-BD-XL-2HRS-TVH, double row, X-life, seals, plastic cage

X-life

Technical information

**Your current product variant**

| | | |
|----------------------------------|------|--|
| Design variant | B | Bearing without filling slot |
| Changed internal design | D | D |
| Type of Sealing | 2HRS | Contact seal on both sides |
| Cage | TVH | Solid cage made of glass-fiber reinforced polyamide PA66 |
| Tolerance class | P6 | Class6 (P6), better than PN |
| Dimensional / heat stabilization | S0 | Rings dimensional stabilized up to 150° |
| Lubricant | GA13 | Ball bearing and insert bearing grease |
| Axial internal clearance | CN | Group N (CN) |

Main Dimensions & Performance Data

| | | |
|-----------------|-------------|-----------------------------------|
| d | 55 mm | Bore diameter |
| D | 100 mm | Outside diameter |
| B | 33,3 mm | Width |
| C _r | 61.000 N | Basic dynamic load rating, radial |
| C _{0r} | 51.000 N | Basic static load rating, radial |
| C _{ur} | 3.550 N | Fatigue load limit, radial |
| n _G | 5.300 1/min | Limiting speed |
| ≈m | 0,95 kg | Weight |



Mounting dimensions

| | | |
|--------------|--------|--------------------------------------|
| $d_{a \min}$ | 64 mm | Minimum diameter shaft shoulder |
| $D_{a \max}$ | 91 mm | Maximum diameter of housing shoulder |
| $r_{a \max}$ | 1,5 mm | Maximum fillet radius |

Dimensions

| | | |
|------------|----------|---|
| r_{\min} | 1,5 mm | Minimum chamfer dimension |
| D_1 | 87,78 mm | Shoulder diameter outer ring |
| D_2 | 90,78 mm | Caliber diameter outer ring |
| d_1 | 71,6 mm | Shoulder diameter inner ring |
| d_2 | 69,18 mm | Caliber diameter inner ring |
| a | 58,4 mm | Distance between the apexes of the pressure cones |
| α | 30 ° | Contact angle |

Temperature range

| | | |
|------------|--------|----------------------------|
| T_{\min} | -20 °C | Operating temperature min. |
| T_{\max} | 100 °C | Operating temperature max. |

Characteristics

| | |
|---|--|
|  | Radial load |
|  | Axial load in one direction |
|  | Axial load in two directions |
|  | Lifetime lubrication, freedom from maintenance |
|  | Grease Lubrication |
|  | Sealed on both sides |