

**FAG****3202-BD-XL-2Z-TVH**

Angular contact ball bearing

Angular contact ball bearing 32..-BD-XL-2Z-TVH, double row, X-life, shields, plastic cage

**X-life**

## Technical information



## Your current product variant

|                                  |      |  |
|----------------------------------|------|--|
| Design variant                   | B    | Bearing without filling slot                             |
| Changed internal design          | D    | D  |
| Sealing                          | 2Z   | Non-contact shield on both sides                         |
| Cage                             | TVH  | Solid cage made of glass-fiber reinforced polyamide PA66 |
| Tolerance class                  | P6   | Class 6 (ISO 492:2023)                                   |
| Dimensional / heat stabilization | SN   | Rings dimensional stabilized up to 120°                  |
| Lubricant                        | GA13 | Ball bearing and insert bearing grease                   |
| Axial internal clearance         | CN   | Group N (CN)   |

## Main Dimensions &amp; Performance Data

|                 |              |                                   |
|-----------------|--------------|-----------------------------------|
| d               | 15 mm        | Bore diameter                     |
| D               | 35 mm        | Outside diameter                  |
| B               | 15,9 mm      | Width                             |
| C <sub>r</sub>  | 12.600 N     | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 7.400 N      | Basic static load rating, radial  |
| C <sub>ur</sub> | 520 N        | Fatigue load limit, radial        |
| n <sub>G</sub>  | 16.700 1/min | Limiting speed                    |
| n <sub>gr</sub> | 18.500 1/min | Reference speed                   |
| m               | 0,064 kg     | Weight                            |



### Mounting dimensions

|              |         |                                      |
|--------------|---------|--------------------------------------|
| $d_{a \min}$ | 19,2 mm | Minimum diameter shaft shoulder      |
| $D_{a \max}$ | 30,8 mm | Maximum diameter of housing shoulder |
| $r_{a \max}$ | 0,6 mm  | Maximum fillet radius                |

### Dimensions

|            |          |   |
|------------|----------|---|
| $r_{\min}$ | 0,6 mm   | Minimum chamfer dimension                         |
| $D_1$      | 29,35 mm | Shoulder diameter outer ring                      |
| $D_2$      | 31,13 mm | Caliber diameter outer ring                       |
| $d_1$      | 22,2 mm  | Shoulder diameter inner ring                      |
| $d_2$      | 20,96 mm | Caliber diameter inner ring                       |
| $a$        | 20,7 mm  | Distance between the apexes of the pressure cones |
| $\alpha$   | 30 °     | Contact angle                                     |

### Temperature range

|            |        |                            |
|------------|--------|----------------------------|
| $T_{\min}$ | -20 °C | Operating temperature min. |
| $T_{\max}$ | 120 °C | Operating temperature max. |

### Characteristics

|   |  |
|---|--|
|  | Radial load                                    |
|  | Axial load in one direction                    |
|  | Axial load in two directions                   |
|  | Lifetime lubrication, freedom from maintenance |
|  | Grease Lubrication                             |
|  | Sealed on both sides                           |