

**FAG****X-life****3203-BD-XL-Z-TVH**

Angular contact ball bearing

Angular contact ball bearing 32..-BD-XL-Z-TVH, double row, X-life, shield , plastic cage

## Technical information

**Your current product variant**

Design variant	B	Bearing without filling slot
Changed internal design	D	D
Type of Seal	Z	Non-contact shield on one Side
Cage	TVH	Solid cage made of glass-fiber reinforced polyamide PA66
Tolerance class	P6	Class6 (P6), better than PN
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	Without	Bearing not greased
Axial internal clearance	CN	Group N (CN)

**Main Dimensions & Performance Data**

d	17 mm	Bore diameter
D	40 mm	Outside diameter
B	17,5 mm	Width
C <sub>r</sub>	15.500 N	Basic dynamic load rating, radial
C <sub>0r</sub>	9.500 N	Basic static load rating, radial
C <sub>ur</sub>	660 N	Fatigue load limit, radial
n <sub>G</sub>	19.400 1/min	Limiting speed
n <sub>gr</sub>	16.600 1/min	Reference speed
m	0,092 kg	Weight



### Mounting dimensions

$d_{a \min}$	21,2 mm	Minimum diameter shaft shoulder
$D_{a \max}$	35,8 mm	Maximum diameter of housing shoulder
$r_{a \max}$	0,6 mm	Maximum fillet radius







### Dimensions

$r_{\min}$	0,6 mm	Minimum chamfer dimension
$D_1$	33,94 mm	Shoulder diameter outer ring
$D_2$	36,09 mm	Caliber diameter outer ring
$d_1$	25,8 mm	Shoulder diameter inner ring
$d_2$	24,43 mm	Caliber diameter inner ring
$a$	23,5 mm	Distance between the apexes of the pressure cones
$\alpha$	30 °	Contact angle

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

### Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Grease Lubrication
	Oil Lubrication
	Sealed on one side