


**FAG****3201-BB-TVH-C3**

Angular contact ball bearing

Angular contact ball bearing 32..-B-TVH,  
double row, plastic cage

## Technical information

**Your current product variant**

Design variant	B	Bearing without filling slot
Changed internal design	B	B
Type of Sealing	Without	Not sealed
Cage	TVH	Solid cage made of glass-fiber reinforced polyamide PA66
Tolerance class	PN	Normal (PN)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	GA13	Ball bearing and insert bearing grease
Axial internal clearance	C3	Group 3 (C3), bigger than CN

**Main Dimensions & Performance Data**

d	12 mm	Bore diameter
D	32 mm	Outside diameter
B	15,9 mm	Width
C <sub>r</sub>	10.500 N	Basic dynamic load rating, radial
C <sub>0r</sub>	5.800 N	Basic static load rating, radial
C <sub>ur</sub>	300 N	Fatigue load limit, radial
n <sub>G</sub>	24.600 1/min	Limiting speed
n <sub>gr</sub>	20.000 1/min	Reference speed
≈m	0,054 kg	Weight



### Mounting dimensions

$d_{a \min}$	16,2 mm	Minimum diameter shaft shoulder
$D_{a \max}$	27,8 mm	Maximum diameter of housing shoulder
$r_{a \max}$	0,6 mm	Maximum fillet radius

### Dimensions

$r_{\min}$	0,6 mm	Minimum chamfer dimension
$D_1$	25,99 mm	Shoulder diameter outer ring
$D_2$	27,77 mm	Caliber diameter outer ring
$d_1$	17,8 mm	Shoulder diameter inner ring
$d_2$	17,2 mm	Caliber diameter inner ring
$a$	16,5 mm	Distance between the apexes of the pressure cones
$\alpha$	25 °	Contact angle

### Temperature range

$T_{\min}$	-20 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

### Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Grease Lubrication
	Oil Lubrication
	Not sealed