

**FAG****3306-BD-XL-C3**

Angular contact ball bearing

Angular contact ball bearing 33.-BD-XL,
double row, X-life, steel sheet metal cage**X-life**

Technical information



Your current product variant

| | | |
|----------------------------------|---------|---|
| Design variant | B | Bearing without filling slot |
| Changed internal design | D | D |
| Sealing | Without | Not sealed |
| Cage | JH | Steel sheet metal |
| Tolerance class | P6 | Class 6 (ISO 492:2023) |
| Dimensional / heat stabilization | SN | Rings dimensional stabilized up to 120° |
| Lubricant | Without | Bearing not greased |
| Axial internal clearance | C3 | Group 3 (C3), bigger than CN |

Main Dimensions & Performance Data

| | | |
|-------------|--------------|-----------------------------------|
| d | 30 mm | Bore diameter |
| D | 72 mm | Outside diameter |
| B | 30,2 mm | Width |
| C_r | 43.000 N | Basic dynamic load rating, radial |
| C_{0r} | 29.500 N | Basic static load rating, radial |
| C_{ur} | 2.050 N | Fatigue load limit, radial |
| n_G | 10.400 1/min | Limiting speed |
| n_{gr} | 8.500 1/min | Reference speed |
| $\approx m$ | 0,55 kg | Weight |



Mounting dimensions

| | | |
|--------------|-------|--------------------------------------|
| $d_{a \min}$ | 37 mm | Minimum diameter shaft shoulder |
| $D_{a \max}$ | 65 mm | Maximum diameter of housing shoulder |
| $r_{a \max}$ | 1 mm | Maximum fillet radius |

Dimensions

| | | |
|------------|----------|---|
| r_{\min} | 1,1 mm | Minimum chamfer dimension |
| D_1 | 60,47 mm | Shoulder diameter outer ring |
| D_2 | 63,46 mm | Caliber diameter outer ring |
| d_1 | 46,25 mm | Shoulder diameter inner ring |
| d_2 | 44,35 mm | Caliber diameter inner ring |
| a | 41,9 mm | Distance between the apexes of the pressure cones |
| α | 30 ° | Contact angle |

Temperature range

| | | |
|------------|--------|----------------------------|
| T_{\min} | -30 °C | Operating temperature min. |
| T_{\max} | 120 °C | Operating temperature max. |

Characteristics

| | |
|---|------------------------------|
|  | Radial load |
|  | Axial load in one direction |
|  | Axial load in two directions |
|  | Grease Lubrication |
|  | Oil Lubrication |
|  | Not sealed |