

**FAG****3306-BD-XL-2HRS-C3**

Angular contact ball bearing



Angular contact ball bearing 33.-BD-XL-2HRS, double row, X-life, seals, steel sheet metal cage

**X-life**

## Technical information



## Your current product variant

Design variant	B	Bearing without filling slot
Changed internal design	D	D
Sealing	2HRS	Contact seal on both sides
Cage	JH	Steel sheet metal
Tolerance class	P6	Class 6 (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	GA13	Ball bearing and insert bearing grease
Axial internal clearance	C3	Group 3 (C3), bigger than CN

## Main Dimensions &amp; Performance Data

d	30 mm	Bore diameter
D	72 mm	Outside diameter
B	30,2 mm	Width
C <sub>r</sub>	43.000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	29.500 N	Basic static load rating, radial
C <sub>ur</sub>	2.050 N	Fatigue load limit, radial
n <sub>G</sub>	7.800 1/min	Limiting speed
≈m	0,56 kg	Weight



### Mounting dimensions

$d_{a \min}$	37 mm	Minimum diameter shaft shoulder
$D_{a \max}$	65 mm	Maximum diameter of housing shoulder
$r_{a \max}$	1 mm	Maximum fillet radius

### Dimensions

$r_{\min}$	1,1 mm	Minimum chamfer dimension
$D_1$	60,47 mm	Shoulder diameter outer ring
$D_2$	63,46 mm	Caliber diameter outer ring
$d_1$	46,25 mm	Shoulder diameter inner ring
$d_2$	44,35 mm	Caliber diameter inner ring
$a$	41,9 mm	Distance between the apexes of the pressure cones
$\alpha$	30 °	Contact angle

### Temperature range

$T_{\min}$	-20 °C	Operating temperature min.
$T_{\max}$	100 °C	Operating temperature max.

### Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Lifetime lubrication, freedom from maintenance
	Grease Lubrication
	Sealed on both sides