

**FAG****3310-BD-XL-2Z-C3**

Angular contact ball bearing

Angular contact ball bearing 33..-BD-XL-2Z, double row, X-life, shields, steel sheet metal cage

**X-life**

## Technical information



## Your current product variant

Design variant	B	Bearing without filling slot
Changed internal design	D	D
Sealing	2Z	Non-contact shield on both sides
Cage	JH	Steel sheet metal
Tolerance class	P6	Class 6 (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Lubricant	GA13	Ball bearing and insert bearing grease
Axial internal clearance	C3	Group 3 (C3), bigger than CN

## Main Dimensions &amp; Performance Data

d	50 mm	Bore diameter
D	110 mm	Outside diameter
B	44,4 mm	Width
C <sub>r</sub>	93.000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	70.000 N	Basic static load rating, radial
C <sub>ur</sub>	4.850 N	Fatigue load limit, radial
n <sub>G</sub>	4.900 1/min	Limiting speed
n <sub>gr</sub>	6.300 1/min	Reference speed
≈m	1,81 kg	Weight



### Mounting dimensions

$d_{a \min}$	61 mm	Minimum diameter shaft shoulder
$D_{a \max}$	99 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2 mm	Maximum fillet radius

### Dimensions

$r_{\min}$	2 mm	Minimum chamfer dimension
$D_1$	93,26 mm	Shoulder diameter outer ring
$D_2$	96,75 mm	Caliber diameter outer ring
$d_1$	71,47 mm	Shoulder diameter inner ring
$d_2$	69,05 mm	Caliber diameter inner ring
$a$	64,2 mm	Distance between the apexes of the pressure cones
$\alpha$	30 °	Contact angle

### Temperature range

$T_{\min}$	-20 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

### Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Lifetime lubrication, freedom from maintenance
	Grease Lubrication
	Sealed on both sides