

**FAG****X-life****3305-BD-XL-TVH-L285-C3**

Angular contact ball bearing

Angular contact ball bearing 33.-BD-XL-TVH, double row, X-life, plastic cage

## Technical information

**Your current product variant**

Design variant	B	Bearing without filling slot
Changed internal design	D	D
Sealing	Without	Not sealed
Cage	TVH	Solid cage made of glass-fiber reinforced polyamide PA66
Tolerance class	P6	Class 6 (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	L285	Grease (L285/customer specific)
Axial internal clearance	C3	Group 3 (C3), bigger than CN

**Main Dimensions & Performance Data**

d	25 mm	Bore diameter
D	62 mm	Outside diameter
B	25,4 mm	Width
C <sub>r</sub>	31.500 N	Basic dynamic load rating, radial
C <sub>0r</sub>	21.000 N	Basic static load rating, radial
C <sub>ur</sub>	1.460 N	Fatigue load limit, radial
n <sub>G</sub>	12.400 1/min	Limiting speed
n <sub>gr</sub>	9.400 1/min	Reference speed
m	0,343 kg	Weight



### Mounting dimensions

$d_{a \min}$	32 mm	Minimum diameter shaft shoulder
$D_{a \max}$	55 mm	Maximum diameter of housing shoulder
$r_{a \max}$	1 mm	Maximum fillet radius

### Dimensions

$r_{\min}$	1,1 mm	Minimum chamfer dimension
$D_1$	51,47 mm	Shoulder diameter outer ring
$D_2$	53,72 mm	Caliber diameter outer ring
$d_1$	39,5 mm	Shoulder diameter inner ring
$d_2$	37,63 mm	Caliber diameter inner ring
$a$	35,4 mm	Distance between the apexes of the pressure cones
$\alpha$	30 °	Contact angle

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

### Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Grease Lubrication
	Not sealed