

**FAG****X-life****3310-BD-XL-TVH-L285-C4**

Angular contact ball bearing

Angular contact ball bearing 33.-BD-XL-TVH, double row, X-life, plastic cage

## Technical information

**Your current product variant**

|                                  |         |  |
|----------------------------------|---------|--|
| Design variant                   | B       | Bearing without filling slot                             |
| Changed internal design          | D       | D  |
| Sealing                          | Without | Not sealed   |
| Cage                             | TVH     | Solid cage made of glass-fiber reinforced polyamide PA66 |
| Tolerance class                  | P6      | Class 6 (ISO 492:2023)                                   |
| Dimensional / heat stabilization | S0      | Rings dimensional stabilized up to 150°                  |
| Lubricant                        | L285    | Grease (L285/customer specific)                          |
| Axial internal clearance         | C4      | Group 4 (C4), bigger than C3                             |

**Main Dimensions & Performance Data**

|                 |             |                                   |
|-----------------|-------------|-----------------------------------|
| d               | 50 mm       | Bore diameter                     |
| D               | 110 mm      | Outside diameter                  |
| B               | 44,4 mm     | Width                             |
| C <sub>r</sub>  | 93.000 N    | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 70.000 N    | Basic static load rating, radial  |
| C <sub>ur</sub> | 4.850 N     | Fatigue load limit, radial        |
| n <sub>G</sub>  | 6.500 1/min | Limiting speed                    |
| n <sub>gr</sub> | 6.300 1/min | Reference speed                   |
| m               | 1,75 kg     | Weight                            |



### Mounting dimensions

|              |       |                                      |
|--------------|-------|--------------------------------------|
| $d_{a \min}$ | 61 mm | Minimum diameter shaft shoulder      |
| $D_{a \max}$ | 99 mm | Maximum diameter of housing shoulder |
| $r_{a \max}$ | 2 mm  | Maximum fillet radius                |


### Dimensions

|            |          |   |
|------------|----------|---|
| $r_{\min}$ | 2 mm     | Minimum chamfer dimension                         |
| $D_1$      | 93,26 mm | Shoulder diameter outer ring                      |
| $d_1$      | 71,47 mm | Shoulder diameter inner ring                      |
| $a$        | 64,2 mm  | Distance between the apexes of the pressure cones |
| $\alpha$   | 30 °     | Contact angle                                     |

### Temperature range

|            |        |                            |
|------------|--------|----------------------------|
| $T_{\min}$ | -20 °C | Operating temperature min. |
| $T_{\max}$ | 120 °C | Operating temperature max. |

### Characteristics



Radial load



Axial load in one direction



Axial load in two directions



Grease Lubrication



Not sealed