


**3812**

## Angular contact ball bearing

Angular contact ball bearing 38..-B-TVH,  
double row, plastic cage

## Technical information



## Your current product variant

Design variant	B	Bearing without filling slot
Type of Seal	Without	Not sealed
Cage	TVH	Solid cage made of glass-fiber reinforced polyamide PA66
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	Without	Bearing not greased
Axial internal clearance	CN	Group N (CN)

## Main Dimensions &amp; Performance Data

d	60 mm	Bore diameter
D	78 mm	Outside diameter
B	14 mm	Width
$C_r$	14.200 N	Basic dynamic load rating, radial
$C_{0r}$	17.100 N	Basic static load rating, radial
$C_{ur}$	970 N	Fatigue load limit, radial
$n_G$	8.800 1/min	Limiting speed
$n_{gr}$	4.700 1/min	Reference speed
$\approx m$	0,146 kg	Weight



### Mounting dimensions

$d_{a \min}$	62 mm	Minimum diameter shaft shoulder
$D_{a \max}$	76 mm	Maximum diameter of housing shoulder
$r_{a \max}$	0,3 mm	Maximum fillet radius

### Dimensions

$r_{\min}$	0,3 mm	Minimum chamfer dimension
$D_1$	72,88 mm	Shoulder diameter outer ring
$D_2$	74,72 mm	Caliber diameter outer ring
$d_1$	67,1 mm	Shoulder diameter inner ring
$d_2$	65,68 mm	Caliber diameter inner ring
$a$	38,1 mm	Distance between the apices of the pressure cones
$\alpha$	25 °	Contact angle

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

### Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Grease Lubrication
	Oil Lubrication
	Not sealed