

**3903-2RS-C3**

Angular contact ball bearing

Angular contact ball bearing 39..-B-2RSR-TVH, double row, seals, plastic cage

Technical information

**Your current product variant**

Design variant	B	Bearing without filling slot
Sealing	2RSR	Contact seal on both sides
Cage	TVH	Solid cage made of glass-fiber reinforced polyamide PA66
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	GA13	Ball bearing and insert bearing grease
Axial internal clearance	C3	Group 3 (C3), bigger than CN

Main Dimensions & Performance Data

d	17 mm	Bore diameter
D	30 mm	Outside diameter
B	10 mm	Width
C_r	5.200 N	Basic dynamic load rating, radial
C_{0r}	4.100 N	Basic static load rating, radial
C_{ur}	213 N	Fatigue load limit, radial
n_G	13.300 1/min	Limiting speed
$\approx m$	0,026 kg	Weight



Mounting dimensions

$d_{a \min}$	19 mm	Minimum diameter shaft shoulder
$D_{a \max}$	28 mm	Maximum diameter of housing shoulder
$r_{a \max}$	0,3 mm	Maximum fillet radius

Dimensions

r_{\min}	0,3 mm	Minimum chamfer dimension
D_1	26,58 mm	Shoulder diameter outer ring
D_2	27,52 mm	Caliber diameter outer ring
d_1	22,55 mm	Shoulder diameter inner ring
d_2	20,1 mm	Caliber diameter inner ring
a	14,9 mm	Distance between the apexes of the pressure cones
α	25 °	Contact angle

Temperature range

T_{\min}	-20 °C	Operating temperature min.
T_{\max}	100 °C	Operating temperature max.

Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Lifetime lubrication, freedom from maintenance
	Grease Lubrication
	Sealed on both sides