

**3908-2RS**

Angular contact ball bearing

Angular contact ball bearing 39..-B-2RS-TVH,
double row, seals, plastic cage

Technical information

**Your current product variant**

Design variant	B	Bearing without filling slot
Sealing	2RS	Contact seal on both sides
Cage	TVH	Solid cage made of glass-fiber reinforced polyamide PA66
Tolerance class	PN	Normal (PN)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	GA13	Ball bearing and insert bearing grease
Axial internal clearance	CN	Group N (CN)

Main Dimensions & Performance Data

d	40 mm	Bore diameter
D	62 mm	Outside diameter
B	16 mm	Width
C_r	17.400 N	Basic dynamic load rating, radial
C_{0r}	16.700 N	Basic static load rating, radial
C_{ur}	870 N	Fatigue load limit, radial
n_G	5.900 1/min	Limiting speed
$\approx m$	0,16 kg	Weight



Mounting dimensions

$d_{a \min}$	43,2 mm	Minimum diameter shaft shoulder
$D_{a \max}$	58,8 mm	Maximum diameter of housing shoulder
$r_{a \max}$	0,6 mm	Maximum fillet radius







Dimensions

r_{\min}	0,6 mm	Minimum chamfer dimension
D_1	55,05 mm	Shoulder diameter outer ring
D_2	56,03 mm	Caliber diameter outer ring
d_1	47,6 mm	Shoulder diameter inner ring
d_2	45,37 mm	Caliber diameter inner ring
a	30 mm	Distance between the apexes of the pressure cones
α	25 °	Contact angle

Temperature range

T_{\min}	-20 °C	Operating temperature min.
T_{\max}	100 °C	Operating temperature max.

Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Lifetime lubrication, freedom from maintenance
	Grease Lubrication
	Sealed on both sides