

**3904-2Z**

## Angular contact ball bearing

Angular contact ball bearing 39..-B-2RZ-TVH,  
double row, shields, plastic cage

## Technical information

**Your current product variant**

Design variant	B	Bearing without filling slot
Sealing	2RZ	Non-contact seal on both sides
Cage	TVH	Solid cage made of glass-fiber reinforced polyamide PA66
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	GA14	Ball bearing grease, low noise
Axial internal clearance	CN	Group N (CN)

**Main Dimensions & Performance Data**

d	20 mm	Bore diameter
D	37 mm	Outside diameter
B	13 mm	Width
C <sub>r</sub>	9.100 N	Basic dynamic load rating, radial
C <sub>0r</sub>	6.800 N	Basic static load rating, radial
C <sub>ur</sub>	355 N	Fatigue load limit, radial
n <sub>G</sub>	15.000 1/min	Limiting speed
n <sub>gr</sub>	12.100 1/min	Reference speed
≈m	55 g	Weight



### Mounting dimensions

$d_{a \min}$	23,2 mm	Minimum diameter shaft shoulder
$D_{a \max}$	33,8 mm	Maximum diameter of housing shoulder
$r_{a \max}$	0,6 mm	Maximum fillet radius

### Dimensions

$r_{\min}$	0,6 mm	Minimum chamfer dimension
$D_1$	32,85 mm	Shoulder diameter outer ring
$D_2$	33,45 mm	Caliber diameter outer ring
$d_1$	27,08 mm	Shoulder diameter inner ring
$d_2$	24,6 mm	Caliber diameter inner ring
$a$	18,8 mm	Distance between the apexes of the pressure cones
$\alpha$	25 °	Contact angle

### Temperature range

$T_{\min}$	-20 °C	Operating temperature min.
$T_{\max}$	100 °C	Operating temperature max.

### Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Lifetime lubrication, freedom from maintenance
	Grease Lubrication
	Sealed on both sides