

**FAG****B7040-C-T-P4S-UL**

Spindle bearing

Spindle bearing B70..-C, adjusted, in pairs or sets, contact angle $\alpha = 15^\circ$, restricted tolerances

Technical information



Your current product variant

Preload	L	Preload light
Contact angle	C	Contact angle 15°
Tolerance class	P4S	Tolerance class P4S, FAG standard better than P4 to DIN 620
Type of Seal	Without	Not sealed
Cage	T	Laminated fabric cage
Arrangement bearing set	U	Single bearing

Main Dimensions & Performance Data

d	200 mm	Bore diameter
D	310 mm	Outside diameter
B	51 mm	Width
C_r	310.000 N	Basic dynamic load rating, radial
C_{0r}	270.000 N	Basic static load rating, radial
C_{ur}	18.000 N	Fatigue load limit, radial
n_G Grease	4.300 1/min	Limiting speed for grease lubrication
n_G Oil	6.700 1/min	Limiting speed for oil lubrication
$\approx m$	11,453 kg	Weight





Mounting dimensions

d_a	217 mm	Diameter shaft shoulder
d_a	h12	Diameter shaft shoulder clearance
D_a	293 mm	Shoulder diameter outer ring
D_a	H12	Shoulder diameter outer ring clearance
$r_{a \max}$	2,1 mm	Maximum recess radius
$r_{a1 \max}$	1 mm	Maximum recess radius
$E_{tk \min}$	232,1 mm	Minimum diameter injection pitch
$E_{tk \max}$	245,4 mm	Maximum diameter injection pitch
$E_{tk1 \min}$	232,1 mm	Minimum diameter injection pitch
$E_{tk1 \max}$	245,4 mm	Maximum diameter injection pitch
a	59,7 mm	Distance between the apexes of the pressure cones

Dimensions

r_{\min}	2,1 mm	Minimum chamfer dimension
$r_{1 \min}$	2,1 mm	Minimum chamfer dimension
α	15 °	Contact angle

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	100 °C	Operating temperature max.



Additional information

F_{VL}	1.791 N	Preload force light
F_{VM}	5.681 N	Preload force medium
F_{VH}	11.402 N	Preload force heavy
K_{aEL}	5.451 N	Lift-off force light
K_{aEM}	18.508 N	Lift-off force medium
K_{aEH}	39.448 N	Lift-off force heavy
c_{aL}	192 N/ μ m	Axial rigidity light
c_{aM}	318 N/ μ m	Axial rigidity medium
c_{aH}	448 N/ μ m	Axial rigidity heavy

Characteristics

-  Radial load
-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed