

**FAG****B71918-C-T-P4S-UL**

## Spindle bearing

Spindle bearing B719...-C, adjusted, in pairs or sets, contact angle  $\alpha = 15^\circ$ , restricted tolerances

## Technical information



## Your current product variant

|                         |         |   |
|-------------------------|---------|---|
| Preload                 | L       | Preload light   |
| Contact angle           | C       | Contact angle $15^\circ$                                    |
| Tolerance class         | P4S     | Tolerance class P4S, FAG standard better than P4 to DIN 620 |
| Type of Seal            | Without | Not sealed  |
| Cage                    | T       | Laminated fabric cage                                       |
| Arrangement bearing set | U       | Single bearing  |

## Main Dimensions &amp; Performance Data

|                 |              |                                       |
|-----------------|--------------|---------------------------------------|
| d               | 90 mm        | Bore diameter                         |
| D               | 125 mm       | Outside diameter                      |
| B               | 18 mm        | Width                                 |
| $C_r$           | 48.000 N     | Basic dynamic load rating, radial     |
| $C_{0r}$        | 35.000 N     | Basic static load rating, radial      |
| $C_{ur}$        | 3.550 N      | Fatigue load limit, radial            |
| $n_G$<br>Grease | 11.000 1/min | Limiting speed for grease lubrication |
| $n_G$ Oil       | 16.000 1/min | Limiting speed for oil lubrication    |
| $\approx m$     | 0,546 kg     | Weight                                |





### Mounting dimensions

|                |          |   |
|----------------|----------|---|
| $d_a$          | 97 mm    | Diameter shaft shoulder                           |
| $d_a$          | h12      | Diameter shaft shoulder clearance                 |
| $D_a$          | 119 mm   | Shoulder diameter outer ring                      |
| $D_a$          | H12      | Shoulder diameter outer ring clearance            |
| $r_{a \max}$   | 0,6 mm   | Maximum recess radius                             |
| $r_{a1 \max}$  | 0,6 mm   | Maximum recess radius                             |
| $E_{tk \min}$  | 100,9 mm | Minimum diameter injection pitch                  |
| $E_{tk \max}$  | 104,3 mm | Maximum diameter injection pitch                  |
| $E_{tk1 \min}$ | 100,9 mm | Minimum diameter injection pitch                  |
| $E_{tk1 \max}$ | 104,3 mm | Maximum diameter injection pitch                  |
| $a$            | 23,4 mm  | Distance between the apexes of the pressure cones |

### Dimensions

|              |        |                           |
|--------------|--------|---------------------------|
| $r_{\min}$   | 1,1 mm | Minimum chamfer dimension |
| $r_{1 \min}$ | 1,1 mm | Minimum chamfer dimension |
| $\alpha$     | 15 °   | Contact angle             |

### Temperature range

|            |        |                            |
|------------|--------|----------------------------|
| $T_{\min}$ | -30 °C | Operating temperature min. |
| $T_{\max}$ | 100 °C | Operating temperature max. |



### Additional information

|           |                |                       |
|-----------|----------------|-----------------------|
| $F_{VL}$  | 238 N          | Preload force light   |
| $F_{VM}$  | 796 N          | Preload force medium  |
| $F_{VH}$  | 1.615 N        | Preload force heavy   |
| $K_{aEL}$ | 729 N          | Lift-off force light  |
| $K_{aEM}$ | 2.628 N        | Lift-off force medium |
| $K_{aEH}$ | 5.691 N        | Lift-off force heavy  |
| $c_{aL}$  | 82 N/ $\mu$ m  | Axial rigidity light  |
| $c_{aM}$  | 140 N/ $\mu$ m | Axial rigidity medium |
| $c_{aH}$  | 200 N/ $\mu$ m | Axial rigidity heavy  |

### Characteristics

-  Radial load
-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed