

**FAG****B71926-E-2RSD-T-P4S-UL**

Spindle bearing

Spindle bearing B719...-E-2RSD, adjusted, in pairs or sets, contact angle $\alpha = 25^\circ$, lip seals on both sides, non-contact, restricted tolerances

Technical information



Your current product variant

Preload	L	Preload light
Contact angle	E	Contact angle 25°
Tolerance class	P4S	Tolerance class P4S, FAG standard better than P4 to DIN 620
Cage	T	Laminated fabric cage
Arrangement bearing set	U	Single bearing
Lubricant	GA21	Grease for super precision bearings, standard

Main Dimensions & Performance Data

d	130 mm	Bore diameter
D	180 mm	Outside diameter
B	24 mm	Width
C_r	85.000 N	Basic dynamic load rating, radial
C_{0r}	67.000 N	Basic static load rating, radial
C_{ur}	5.700 N	Fatigue load limit, radial
n_G Grease	6.700 1/min	Limiting speed for grease lubrication
$\approx m$	1,529 kg	Weight



Mounting dimensions

d_a	139 mm	Diameter shaft shoulder
d_a	H12	Diameter shaft shoulder clearance
D_a	171 mm	Shoulder diameter outer ring
D_a	H12	Shoulder diameter outer ring clearance
$r_{a \max}$	0,6 mm	Maximum recess radius
$r_{a1 \max}$	0,6 mm	Maximum recess radius
a	48,1 mm	Distance between the apexes of the pressure cones

Dimensions

r_{\min}	1,5 mm	Minimum chamfer dimension
$r_{1 \min}$	1,5 mm	Minimum chamfer dimension
α	25 °	Contact angle

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	80 °C	Operating temperature max.

Additional information

F_{VL}	711 N	Preload force light
F_{VM}	2.466 N	Preload force medium
F_{VH}	5.161 N	Preload force heavy
K_{aEL}	2.064 N	Lift-off force light
K_{aEM}	7.379 N	Lift-off force medium
K_{aEH}	15.916 N	Lift-off force heavy
c_{aL}	275 N/ μ m	Axial rigidity light
c_{aM}	438 N/ μ m	Axial rigidity medium
c_{aH}	590 N/ μ m	Axial rigidity heavy



Characteristics



Radial load



Axial load in one direction



Lifetime lubrication, freedom from maintenance



Grease Lubrication



Sealed on both sides