

**FAG****B7208-E-2RSD-T-P4S-UL**

## Spindle bearing

Spindle bearing B72...-E-2RSD, adjusted, in pairs or sets, contact angle  $\alpha = 25^\circ$ , lip seals on both sides, non-contact, restricted tolerances

## Technical information



## Your current product variant

Preload	L	Preload light
Contact angle	E	Contact angle 25°
Tolerance class	P4S	Tolerance class P4S, FAG standard better than P4 to DIN 620
Cage	T	Laminated fabric cage
Arrangement bearing set	U	Single bearing
Lubricant	GA21	Grease for super precision bearings, standard

## Main Dimensions &amp; Performance Data

d	40 mm	Bore diameter
D	80 mm	Outside diameter
B	18 mm	Width
C <sub>r</sub>	31.000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	15.400 N	Basic static load rating, radial
C <sub>ur</sub>	1.630 N	Fatigue load limit, radial
n <sub>G</sub> Grease	17.000 1/min	Limiting speed for grease lubrication
≈m	375 g	Weight



### Mounting dimensions

$d_a$	48 mm	Diameter shaft shoulder
$d_a$	h12	Diameter shaft shoulder clearance
$D_a$	72 mm	Shoulder diameter outer ring
$D_a$	H12	Shoulder diameter outer ring clearance
$r_{a \max}$	1 mm	Maximum recess radius
$r_{a1 \max}$	0,6 mm	Maximum recess radius
$a$	23 mm	Distance between the apexes of the pressure cones

### Dimensions

$r_{\min}$	1,1 mm	Minimum chamfer dimension
$r_{1 \min}$	1,1 mm	Minimum chamfer dimension
$\alpha$	25 °	Contact angle

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	80 °C	Operating temperature max.

### Additional information

$F_{VL}$	257 N	Preload force light
$F_{VM}$	906 N	Preload force medium
$F_{VH}$	1.903 N	Preload force heavy
$K_{aEL}$	750 N	Lift-off force light
$K_{aEM}$	2.748 N	Lift-off force medium
$K_{aEH}$	5.985 N	Lift-off force heavy
$c_{aL}$	114 N/ $\mu$ m	Axial rigidity light
$c_{aM}$	184 N/ $\mu$ m	Axial rigidity medium
$c_{aH}$	252 N/ $\mu$ m	Axial rigidity heavy



### Characteristics

---



Radial load



Axial load in one direction



Lifetime lubrication, freedom from maintenance



Grease Lubrication



Sealed on both sides