

**FAG****HCB7028-C-T-P4S-UL**

Spindle bearing

Spindle bearing HCB70...-C, adjusted, in pairs or sets, contact angle $\alpha = 15^\circ$, with ceramic balls, restricted tolerances

Technical information



Your current product variant

Contact angle	C	Contact angle 15°
Sealing	Without	Not sealed
Cage	T	Laminated fabric cage
Tolerance class	P4S	Tolerance class P4S, FAG standard better than P4 to DIN 620
Arrangement bearing set	U	Single bearing
Preload	L	Preload light

Main Dimensions & Performance Data

d	140 mm	Bore diameter
D	210 mm	Outside diameter
B	33 mm	Width
C_r	153.000 N	Basic dynamic load rating, radial
C_{0r}	109.000 N	Basic static load rating, radial
C_{ur}	6.600 N	Fatigue load limit, radial
n_G Grease	9.000 1/min	Limiting speed for grease lubrication
n_G Oil	14.000 1/min	Limiting speed for oil lubrication
$\approx m$	3,34 kg	Weight





Mounting dimensions

d_a	152 mm	Diameter shaft shoulder
d_a	h12	Diameter shaft shoulder clearance
D_a	199 mm	Shoulder diameter outer ring
D_a	H12	Shoulder diameter outer ring clearance
$r_{a \max}$	2 mm	Maximum recess radius
$r_{a1 \max}$	1 mm	Maximum recess radius
$E_{tk \min}$	161,6 mm	Minimum diameter injection pitch
$E_{tk \max}$	169,2 mm	Maximum diameter injection pitch
$E_{tk1 \min}$	161,6 mm	Minimum diameter injection pitch
$E_{tk1 \max}$	169,2 mm	Maximum diameter injection pitch
a	39,9 mm	Distance between the apexes of the pressure cones

Dimensions

r_{\min}	2 mm	Minimum chamfer dimension
$r_{1 \min}$	2 mm	Minimum chamfer dimension
α	15 °	Contact angle

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	100 °C	Operating temperature max.



Additional information

F_{VL}	471 N	Preload force light
F_{VM}	1.553 N	Preload force medium
F_{VH}	3.179 N	Preload force heavy
K_{aEL}	1.402 N	Lift-off force light
K_{aEM}	4.871 N	Lift-off force medium
K_{aEH}	10.483 N	Lift-off force heavy
c_{aL}	125 N/ μ m	Axial rigidity light
c_{aM}	203 N/ μ m	Axial rigidity medium
c_{aH}	282 N/ μ m	Axial rigidity heavy

Characteristics

-  Radial load
-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed