



**FAG**

**HCB7203-C-T-P4S-UL**

Spindle bearing

Spindle bearing HCB72...-C, adjusted, in pairs or sets, contact angle  $\alpha = 15^\circ$ , with ceramic balls, restricted tolerances

Technical information



Your current product variant

Contact angle	C	Contact angle 15°
Sealing	Without	Not sealed
Cage	T	Laminated fabric cage
Tolerance class	P4S	Tolerance class P4S, FAG standard better than P4 to ISO 492:2023
Arrangement bearing set	U	Single bearing
Preload	L	Preload light

Main Dimensions & Performance Data

d	17 mm	Bore diameter
D	40 mm	Outside diameter
B	12 mm	Width
$C_r$	13.000 N	Basic dynamic load rating, radial
$C_{0r}$	5.600 N	Basic static load rating, radial
$C_{ur}$	450 N	Fatigue load limit, radial
$n_G$ Grease	50.000 1/min	Limiting speed for grease lubrication
$n_G$ Oil	75.000 1/min	Limiting speed for oil lubrication
$\approx m$	55 g	Weight





### Mounting dimensions

$d_a$	22,5 mm	Diameter shaft shoulder
$d_a$	h12	Diameter shaft shoulder clearance
$D_a$	34,5 mm	Shoulder diameter outer ring
$D_a$	H12	Shoulder diameter outer ring clearance
$r_{a \max}$	0,6 mm	Maximum recess radius
$r_{a1 \max}$	0,3 mm	Maximum recess radius
$E_{tk \min}$	25 mm	Minimum diameter injection pitch
$E_{tk \max}$	26,7 mm	Maximum diameter injection pitch
$E_{tk1 \min}$	25 mm	Minimum diameter injection pitch
$E_{tk1 \max}$	26,7 mm	Maximum diameter injection pitch
$a$	9,8 mm	Distance between the apexes of the pressure cones

### Dimensions

$r_{\min}$	0,6 mm	Minimum chamfer dimension
$r_{1 \min}$	0,6 mm	Minimum chamfer dimension
$\alpha$	15 °	Contact angle

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	100 °C	Operating temperature max.



### Additional information

$F_{VL}$	25 N	Preload force light
$F_{VM}$	97 N	Preload force medium
$F_{VH}$	208 N	Preload force heavy
$K_{aEL}$	75 N	Lift-off force light
$K_{aEM}$	313 N	Lift-off force medium
$K_{aEH}$	708 N	Lift-off force heavy
$c_{aL}$	20 N/ $\mu$ m	Axial rigidity light
$c_{aM}$	34 N/ $\mu$ m	Axial rigidity medium
$c_{aH}$	50 N/ $\mu$ m	Axial rigidity heavy

### Characteristics

-  Radial load
-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed